


Part number

BE 3265



Interlocked switched socket-outlet, BE series, 3 poles + N + PE, 6 h (red), 32 A, 200/346 ÷ 240/415 V, without fuse-carrier

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | BE |
| N. of poles | 3 poles + N +  |
| Clock position | 6 |
| Size | Socket centre distance 114 x 228 mm |
| Specification | Without fuse-carrier |

Technical data

| | |
|--------------------------------|---------------------|
| Current | 32 A |
| Voltage | 200/346 ÷ 240/415 V |
| IP degree of protection | IP67 |

Further technical details

| | |
|--|-----------------|
| Weight | 1.320,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 3000 red |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747003728 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|----------------------|
| Sub-packaging length | 116,00 mm |
| Sub-packaging height | 130,00 mm |
| Sub-packaging width | 230,00 mm |
| Sub-packaging weight | 1,32 kg |
| Sub-packaging volume | 3,47 dm ³ |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747003735 |