


Part number
BK 3245



Interlocked switched socket-outlet, BK series,
 3 poles + N + PE, 4 h (yellow), 32 A, 57/100 ÷
 75/130 V, sectionable fuse carrier 10 x 38 mm

| Product description | | Material properties | |
|--|---|----------------------------------|---|
| Product type | Interlocked switched socket-outlet | Colour | RAL 7035 grey, RAL 1021 yellow |
| Series | BK | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 3 poles + N +  | RoHs conformity | 6(c): copper alloy containing up to 4% lead by weight |
| Clock position | 4 | China RoHs - EFUP | 50 |
| Size | Socket centre distance 114 x 228 mm | REACH SVHC substances | Yes Lead |
| Specification | Sectionable fuse carrier 10 x 38 mm | SCIP number | F6799547-ab84-42f2-938f-233ba663766d |
| Technical data | | Approvals / Standards | |
| Current | 32 A | Reference standard | EN 60309-1, -2 e -4 |
| Voltage | 57/100 ÷ 75/130 V | General ordering information | |
| IP degree of protection | IP67 | EAN13 code | 8015747004817 |
| Further technical details | | Packaging Information | |
| Weight | 1.420,00 g | Sub-packaging length | 116,00 mm |
| Operating temperature range (min, max) | -25°C ... +40°C | Sub-packaging height | 130,00 mm |
| IK rating (impact degree of protection) | IK10 | Sub-packaging width | 230,00 mm |
| | | Sub-packaging weight | 1,42 kg |
| | | Sub-packaging volume | 3,47 dm ³ |
| | | Sub-packaging description | Carton box |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747004831 |

Part number

BK 3245



Catalogue drawings



| BK | | A | B |
|-----|------------|-----|----|
| 16A | 2P + ⊕ | 105 | 50 |
| | 3P + ⊕ | 105 | 50 |
| | 3P + N + ⊕ | 110 | 50 |
| 32A | 2P + ⊕ | 140 | 58 |
| | 3P + ⊕ | 140 | 58 |
| | 3P + N + ⊕ | 140 | 58 |