

Part number

C30MA 25 P



Male crimp contact, C30 series, 300 A, turned silver plated, wire cross section 25 mm², AWG 4, finger-proof version

Product description

| | |
|----------------------|----------------------|
| Product type | Crimp contact |
| Series | C30 |
| Gender | Male |
| Specification | Finger-proof version |

Technical data

| | |
|---------------------------|-----------------------|
| Current | 300 A |
| Wire cross-section | 25,00 mm ² |
| AWG size | 4 |
| Contact type | Turned silver plated |

Further technical details

| | |
|------------------------------------|----------|
| Contact resistance | ≤ 0,2 mΩ |
| Weight | 26,90 g |
| Conductors stripping length | 19 mm |

Material properties

| | |
|------------------------------|--------------------------------------------------------------------------------|
| Main material | Copper alloy |
| Other materials | Cap: polycarbonate (PC) |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747290708 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|----------------------|
| Packaging length | 112,00 mm |
| Packaging height | 95,00 mm |
| Packaging width | 117,00 mm |
| Packaging volume | 1,24 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 40 Pcs |
| Packaging EAN code | 8015747290715 |
| Sub-packaging description | Plastic box |
| Sub-packaging quantity | 5 Pcs |
| Sub-packaging EAN barcode | 8015747290722 |