

Part number

CCMJD 4.0



Male crimp contact, CC series, 16 A, turned gold plated, wire cross section 4 mm², AWG 12, basic gold plating

| Product description | | Material properties | |
|------------------------------------|----------------------|----------------------------------|---|
| Product type | Crimp contact | Main material | Copper alloy |
| Series | CC | | Compliant with exemption |
| Gender | Male | RoHs conformity | 6(c): copper alloy containing up to 4% lead by weight |
| Specification | Basic gold plating | China RoHs - EFUP | 50 |
| Technical data | | REACH SVHC substances | Yes Lead |
| Current | 16 A | SCIP number | C0979fba-9907-458f-a94a-db781440f273 |
| Wire cross-section | 4,00 mm ² | Approvals / Standards | |
| AWG size | 12 | Certifications | CSA, EAC |
| Contact type | Turned gold plated | UL | ECBT2 |
| Further technical details | | General ordering information | |
| Weight | 1,35 g | EAN13 code | 8015747076630 |
| Conductors stripping length | 7,5 mm | eCl@ss 8.1 | 27440204 |
| | | ETIM 7.0 | EC000796 |
| | | Packaging Information | |
| | | Packaging length | 112,00 mm |
| | | Packaging height | 95,00 mm |
| | | Packaging width | 117,00 mm |
| | | Packaging weight | 1,30 kg |
| | | Packaging volume | 1,24 dm ³ |
| | | Packaging description | Carton box |
| | | Packaging quantity | 800 Pcs |
| | | Packaging EAN code | 8015747207430 |
| | | Sub-packaging length | 50,00 mm |
| | | Sub-packaging height | 44,00 mm |
| | | Sub-packaging width | 50,00 mm |
| | | Sub-packaging weight | 0,16 kg |
| | | Sub-packaging volume | 0,11 dm ³ |
| | | Sub-packaging description | Plastic box |
| | | Sub-packaging quantity | 100 Pcs |
| | | Sub-packaging EAN barcode | 8015747094122 |

Part number

CCMJD 4.0



Catalogue drawings



CCFJD and CCMJD contacts

| conductor section mm ² | conductor slot $\varnothing A$ (mm) | conductors stripping length mm |
|--------------------------------------|--|-----------------------------------|
| 0,14-0,37 | 0,9 | 7,5 |
| 0,5 | 1,1 | 7,5 |
| 0,75 | 1,3 | 7,5 |
| 1,0 | 1,45 | 7,5 |
| 1,5 | 1,8 | 7,5 |
| 2,5 | 2,2 | 7,5 |
| 3,0 | 2,55 | 7,5 |
| 4,0 | 2,85 | 7,5 |