

Part number

# CIFA 0.5



Female crimp contact, CI series, 5 A, turned silver plated, wire cross section 0,33 - 0,52 mm<sup>2</sup>, AWG 22 - 20


Product description		Material properties	
<b>Product type</b>	Crimp contact	<b>Main material</b>	Copper alloy
<b>Series</b>	CI		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>Gender</b>	Female	<b>RoHs conformity</b>	6(c): copper alloy containing up to 4% lead by weight
Technical data		<b>China RoHs - EFUP</b>	50
<b>Current</b>	5 A	<b>REACH SVHC substances</b>	Yes
<b>Wire cross-section</b>	0,33 mm <sup>2</sup> - 0,52 mm <sup>2</sup>		Lead
<b>AWG size</b>	22 - 20	<b>SCIP number</b>	C0979fba-9907-458f-a94a-db781440f273
<b>Contact type</b>	Turned silver plated	Approvals / Standards	
Further technical details		<b>Certifications</b>	CSA, EAC
<b>Weight</b>	0,24 g	<b>UL</b>	ECBT2
<b>Conductors stripping length</b>	4 mm	General ordering information	
		<b>EAN13 code</b>	8015747212755
		<b>eCl@ss 8.1</b>	27440204
		<b>ETIM 7.0</b>	EC000796
		Packaging Information	
		<b>Packaging weight</b>	0,29 kg
		<b>Packaging description</b>	Carton box
		<b>Packaging quantity</b>	1000 Pcs
		<b>Packaging EAN code</b>	8015747258500
		<b>Sub-packaging length</b>	75,00 mm
		<b>Sub-packaging height</b>	89,00 mm
		<b>Sub-packaging width</b>	110,00 mm
		<b>Sub-packaging volume</b>	0,73 dm <sup>3</sup>
		<b>Sub-packaging description</b>	Plastic bag
		<b>Sub-packaging quantity</b>	25 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747212816

Part number

# CIFA 0.5



## Catalogue drawings



### CIF contacts

conductor section mm <sup>2</sup>	conductor slot ø A (mm)	conductors stripping length (mm)
0,08-0,21	0,64	4
0,13-0,33	0,90	4
0,33-0,52	1,12	4

max insulation diameter: 1,7 mm