

Part number

CX7FA 25



Female crimp contact, CX7 series, 70 A, turned silver plated, wire cross section 25 mm², AWG 4 - 3

Product description

Product type	Crimp contact
Series	CX7
Gender	Female

Technical data

Current	70 A
Wire cross-section	25,00 mm ²
AWG size	4 - 3
Contact type	Turned silver plated

Further technical details

Mating cycles	≥ 500
Contact resistance	≤ 0,5 mΩ
Weight	9,50 g
Operating temperature range (min, max)	-40°C ... +125°C
Conductors stripping length	15 mm

Material properties

Main material	Copper alloy
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	C0979fba-9907-458f-a94a-db781440f273

Approvals / Standards

Certifications	CSA, EAC
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747182515
eCl@ss 8.1	27440204
ETIM 7.0	EC000796

Packaging Information

Sub-packaging length	50,00 mm
Sub-packaging height	44,00 mm
Sub-packaging width	50,00 mm
Sub-packaging weight	0,15 kg
Sub-packaging volume	0,11 dm ³
Sub-packaging description	Plastic box
Sub-packaging quantity	16 Pcs
Sub-packaging EAN barcode	8015747182591

Part number

CX7FA 25



Catalogue drawings

PART NUMBERS SILVER PLATED	$\varnothing A$ mm	WIRE GAUGE		STRIPPING LENGTH mm
		mm ²	AWG	
CX7FA 6.0	3,5	6	10	15
CX7FA 10	4,3	10	7	
CX7FA 16	5,5	16	5	
CX7FA 25	7,0	25	3	

Catalogue drawings

