


Part number

KI 1695 IB6



Interlocked switched socket-outlet, IB6 series, 3 poles + N + PE, 9 h (blue), 16 A, 200 ÷ 250 V, sectionable fuse carrier 10 x 38 mm

Product description	
Product type	Interlocked switched socket-outlet
Series	KI...IB6
N. of poles	3 poles + N + 
Clock position	9
Size	114x228 fixing plates FC xx41 TB
Cable entry	M25
Specification	Sectionable fuse carrier 10 x 38 mm
Technical data	
Current	16 A
Voltage	200 ÷ 250 V
IP degree of protection	IP66
Further technical details	
Weight	980,00 g
Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10

Material properties	
Colour	RAL 7035 grey, RAL 5015 blue
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4
General ordering information	
EAN13 code	8015747199483
Packaging Information	
Packaging length	520,00 mm
Packaging height	305,00 mm
Packaging width	490,00 mm
Packaging weight	15,10 kg
Packaging volume	77,71 dm ³
Packaging description	Carton box
Packaging quantity	15 Pcs
Packaging EAN code	8015747245821
Sub-packaging length	270,00 mm
Sub-packaging height	125,00 mm
Sub-packaging width	120,00 mm
Sub-packaging weight	1,01 kg
Sub-packaging volume	4,05 dm ³
Sub-packaging description	Carton box
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747245838