


Part number

KI 6364 IB6



Interlocked switched socket-outlet, IB6 series,
3 poles + PE, 6 h (red), 63 A, 380 ÷ 415 V,
sectionable fuse carrier 22 x 58 mm

Product description	
Product type	Interlocked switched socket-outlet
Series	KI...IB6
N. of poles	3 poles + 
Clock position	6
Size	143x343 fixing plates FC xx53 TB
Cable entry	M40
Specification	Sectionable fuse carrier 22 x 58 mm
Technical data	
Current	63 A
Voltage	380 ÷ 415 V
IP degree of protection	IP66
Further technical details	
Weight	3.450,00 g
Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10

Material properties	
Colour	RAL 7035 grey, RAL 3000 red
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4
General ordering information	
EAN13 code	8015747201179
Packaging Information	
Packaging weight	3,60 kg
Packaging description	Carton box
Packaging quantity	1 Pcs
Packaging EAN code	8015747201186
Sub-packaging length	150,00 mm
Sub-packaging height	188,00 mm
Sub-packaging width	430,00 mm
Sub-packaging weight	3,60 kg
Sub-packaging volume	12,13 dm ³
Sub-packaging description	Plastic packaging
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747201193