

Part number

# MFON 24.32



Hood, LS-TYPE series, with 4 pegs, M32 side cable entry without adapter, size "104.27", high construction

Product description		Material properties	
<b>Product type</b>	Hood	<b>Colour</b>	RAL 9005 black
<b>Series</b>	LS-TYPE	<b>RoHs conformity</b>	Compliant
<b>Closing type</b>	With 4 pegs	<b>China RoHs - EFUP</b>	E
<b>Size</b>	Size 104.27	<b>REACH SVHC substances</b>	No
<b>Cable entry</b>	Side cable entry M32	<b>Approvals / Standards</b>	
<b>Specification</b>	High construction	<b>Certifications</b>	DNV, BV
<b>Technical data</b>		<b>UL</b>	ECBT2
<b>IP degree of protection</b>	IP65	<b>cUL</b>	ECBT8
<b>Further technical details</b>		<b>General ordering information</b>	
<b>Weight</b>	236,00 g	<b>EAN13 code</b>	8015747019330
<b>Operating temperature range (min, max)</b>	-40°C...+125°C	<b>eCl@ss 8.1</b>	27440202
		<b>ETIM 7.0</b>	EC000437
		<b>Packaging Information</b>	
		<b>Sub-packaging weight</b>	1,18 kg
		<b>Sub-packaging description</b>	Plastic packaging
		<b>Sub-packaging quantity</b>	5 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747187756

# Part number MFON 24.32



Catalogue drawings



Catalogue drawings

**CH..N - MA, MF..N enclosures**      size "104.27"      LS-TYPE version

<p>inserts:      page</p> <p>CD ..... 64 poles + @ 51+53 *</p> <p>CT, CTS **) ..... 64 poles + @ 57 *</p> <p>CDD ..... 108 poles + @ 64+66 *</p> <p>CDE ..... 46 poles + @ 83+85 *</p> <p>CSH ..... 24 poles + @ 91+93 *</p> <p>CCE ..... 24 poles + @ 100+104 *</p> <p>CNE, CSE, JCNE, JCSE 24 poles + @ 101 and 109 *</p> <p>CSS ..... 24 poles + @ 122+123 *</p> <p>CTE, CTSE **) ..... 24 poles + @ 129 *</p> <p>CMSE ..... 10+2 (aux) poles + @ 139 *</p> <p>CMCE ..... 10+2 (aux) poles + @ 138 *</p> <p>CX ..... 4/8 poles + @ 155 *</p> <p>MIXO ..... 6 modules 160+195 *</p> <p>insert centre distance: 104 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p><b> housings with double lever</b></p>	<p><b> hoods with 4 pegs</b></p>																					
<table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"><b>description</b></td> <td style="width: 25%;"><b>part no.</b></td> <td style="width: 25%;"><b>entry</b></td> </tr> <tr> <td>bulkhead mounting housing, with 2 levers</td> <td><b>CHIN 24</b></td> <td><b>M</b></td> </tr> <tr> <td>surface mounting housing, high construction, with 2 levers</td> <td><b>MAPN 24.32</b></td> <td><b>32</b></td> </tr> <tr> <td>with pegs, side entry</td> <td></td> <td><b>MHON 24.32 32</b></td> </tr> <tr> <td>with pegs, side entry, high construction</td> <td></td> <td><b>MFON 24.32 32</b></td> </tr> <tr> <td>with pegs, side entry</td> <td></td> <td><b>MHVN 24.32 32</b></td> </tr> <tr> <td>with pegs, side entry, high construction</td> <td></td> <td><b>MFVN 24.32 32</b></td> </tr> </table>	<b>description</b>	<b>part no.</b>	<b>entry</b>	bulkhead mounting housing, with 2 levers	<b>CHIN 24</b>	<b>M</b>	surface mounting housing, high construction, with 2 levers	<b>MAPN 24.32</b>	<b>32</b>	with pegs, side entry		<b>MHON 24.32 32</b>	with pegs, side entry, high construction		<b>MFON 24.32 32</b>	with pegs, side entry		<b>MHVN 24.32 32</b>	with pegs, side entry, high construction		<b>MFVN 24.32 32</b>	<p><b> dimensions in mm</b></p> <p><b>CHIN 24</b></p> <p><b>MAPN 24.32</b></p>	<p><b> dimensions in mm</b></p> <p><b>MFON 24.32</b></p> <p><b>MFVN 24.32</b></p> <p><b>MHON 24.32</b></p> <p><b>MHVN 24.32</b></p>
<b>description</b>	<b>part no.</b>	<b>entry</b>																					
bulkhead mounting housing, with 2 levers	<b>CHIN 24</b>	<b>M</b>																					
surface mounting housing, high construction, with 2 levers	<b>MAPN 24.32</b>	<b>32</b>																					
with pegs, side entry		<b>MHON 24.32 32</b>																					
with pegs, side entry, high construction		<b>MFON 24.32 32</b>																					
with pegs, side entry		<b>MHVN 24.32 32</b>																					
with pegs, side entry, high construction		<b>MFVN 24.32 32</b>																					
<p>**) only in the CHIN 24 enclosure</p> <p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p> <div style="text-align: center;"> <p>IP65</p> </div> <p>dimensions shown are not binding and may be changed without notice</p>																							