

Part number

MFVN 16 G32



Hood, LS-TYPE series, with 2 levers, M32 top cable entry without adapter, size "77.27", high construction

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 2 levers
Size	Size 77.27
Cable entry	Top cable entry M32
Specification	High construction

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	330,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747187411
eCl@ss 8.1	27440202
ETIM 7.0	EC000437


Packaging Information

Sub-packaging weight	1,65 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747188197

Part number MFVN 16 G32



Catalogue drawings



Catalogue drawings

CH..N - MF..N enclosures		size "77.27"	LS-TYPE version
<p>inserts: page</p> <p>CD 40 poles + @ 49+52 *</p> <p>CDD 72 poles + @ 62+65 *</p> <p>CQE 32 poles + @ 82+84 *</p> <p>CSH 16 poles + @ 90+92 *</p> <p>CCE 16 poles + @ 93+102 *</p> <p>CNE, CSE, JONE, JCSE 16 poles + @ 99 and 108 *</p> <p>CSS 16 poles + @ 120+122 *</p> <p>CMSE 6+2 (aux) poles + @ 137 *</p> <p>CMCE 6+2 (aux) poles + @ 136 *</p> <p>CP 6 poles + @ 149+150 *</p> <p>CX 6/36 e 12/2 poles + @ 152+153 *</p> <p>CX 4/0 e 4/2 poles + @ 154 *</p> <p>MIXO 4 modules 160+195 *</p> <p>insert centre distance: 77,5 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p>hoods with 4 pegs</p>	<p>covers</p>	
<p>description</p> <p>with 2 levers and gasket, top entry</p> <p>with 2 levers and gasket, top entry, high construction</p> <p>cover with pegs</p> <p>cover with 2 levers</p>	<p>part no.</p> <p>MHVN 16 G32 32</p> <p>MFVN 16 G32 32</p>	<p>entry</p> <p>M</p>	<p>part no.</p> <p>CHCN 16</p> <p>CHCN 16 G</p>
<p>- kiln powder coating with RAL 9005 black epoxy polyester powder</p> <p>- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>	<p>dimensions in mm</p> <p>MHVN 16 G32</p> <p>MFVN 16 G32</p>	<p>dimensions in mm</p> <p>CHCN 16</p> <p>CHCN 16 G</p>	
<p>IP65</p> <p>dimensions shown are not binding and may be changed without notice</p>			