

Part number

MFVN 24.32




Hood, LS-TYPE series, with 4 pegs, M32 top cable entry without adapter, size "104.27", high construction

Product description		Material properties	
Product type	Hood	Colour	RAL 9005 black
Series	LS-TYPE	RoHs conformity	Compliant
Closing type	With 4 pegs	China RoHs - EFUP	E
Size	Size 104.27	REACH SVHC substances	No
Cable entry	Top cable entry M32	Approvals / Standards	
Specification	High construction	Certifications	DNV, BV
Technical data		UL	ECBT2
IP degree of protection	IP65	cUL	ECBT8
Further technical details		General ordering information	
Operating temperature range (min, max)	-40°C...+125°C	EAN13 code	8015747163606
		eCl@ss 8.1	27440202
		ETIM 7.0	EC000437
		Packaging Information	
		Sub-packaging description	Plastic packaging
		Sub-packaging quantity	5 Pcs
		Sub-packaging EAN barcode	8015747187824

Part number MFVN 24.32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "104.27" LS-TYPE version

<p>inserts: page</p> <p>CD 64 poles + ⊕ 51+53 *</p> <p>CT, CTS **) 64 poles + ⊕ 57 *</p> <p>CDD 108 poles + ⊕ 64+66 *</p> <p>CDE 46 poles + ⊕ 83+85 *</p> <p>CSH 24 poles + ⊕ 91+93 *</p> <p>CCE 24 poles + ⊕ 100+104 *</p> <p>CNE, CSE, JCNE, JCSE 24 poles + ⊕ 101 and 109 *</p> <p>CSS 24 poles + ⊕ 122+123 *</p> <p>CTE, CTSE **) 24 poles + ⊕ 129 *</p> <p>CMSE 10+2 (aux) poles + ⊕ 139 *</p> <p>CMCE 10+2 (aux) poles + ⊕ 138 *</p> <p>CX 4/8 poles + ⊕ 155 *</p> <p>MIXO 6 modules 160+195 *</p> <p>insert centre distance: 104 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p> housings with double lever</p>	<p> hoods with 4 pegs</p>
description	part no. entry	part no. entry
bulkhead mounting housing, with 2 levers	CHIN 24	
surface mounting housing, high construction, with 2 levers	MAPN 24.32 32	
with pegs, side entry		MHON 24.32 32
with pegs, side entry, high construction		MFON 24.32 32
with pegs, side entry		MHVN 24.32 32
with pegs, side entry, high construction		MFVN 24.32 32
**) only in the CHIN 24 enclosure		
<p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>	<p>dimensions in mm</p> <p>CHIN 24</p> <p>MAPN 24.32</p>	<p>dimensions in mm</p> <p>MFON 24.32</p> <p>MFVN 24.32</p> <p>MHON 24.32</p> <p>MHVN 24.32</p>
	<p>dimensions shown are not binding and may be changed without notice</p>	