

Part number

# MHON 10.25



Hood, LS-TYPE series, with 4 pegs, M25 side cable entry, size "57.27"

#### Product description

<b>Product type</b>	Hood
<b>Series</b>	LS-TYPE
<b>Closing type</b>	With 4 pegs
<b>Size</b>	Size 57.27
<b>Cable entry</b>	Side cable entry M25

#### Technical data

<b>IP degree of protection</b>	IP65
--------------------------------	------

#### Further technical details

<b>Weight</b>	120,00 g
<b>Operating temperature range (min, max)</b>	-40°C...+125°C

#### Material properties

<b>Colour</b>	RAL 9005 black
<b>RoHs conformity</b>	Compliant
<b>China RoHs - EFUP</b>	E
<b>REACH SVHC substances</b>	No

#### Approvals / Standards

<b>Certifications</b>	DNV, BV
<b>UL</b>	ECBT2
<b>cUL</b>	ECBT8

#### General ordering information

<b>EAN13 code</b>	8015747194242
<b>eCl@ss 8.1</b>	27440202
<b>ETIM 7.0</b>	EC000437

#### Packaging Information

<b>Sub-packaging weight</b>	0,60 kg
<b>Sub-packaging description</b>	Plastic packaging
<b>Sub-packaging quantity</b>	5 Pcs
<b>Sub-packaging EAN barcode</b>	8015747195140

# Part number MHON 10.25



Catalogue drawings



Catalogue drawings

**CH..N - MA, MF..N enclosures** size "57.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CDD .....	42 poles + @ 61 *		
CQE .....	18 poles + @ 81 *		
CSH .....	10 poles + @ 89 *		
CCE .....	10 poles + @ 90 *		
CNE, CSE, JONE, JCSE .....	10 poles + @ 97 and 107 *		
CSS .....	10 poles + @ 119 *		
CTE, CTSE **) .....	10 poles + @ 127 *		
CMSE .....	3+2 (aux) poles + @ 135 *		
CMCE .....	3+2 (aux) poles + @ 134 *		
CX .....	8/24 poles + @ 151 *		
MIXO .....	3 modules 160+195 *		

insert centre distance: 57 x 27 mm

\* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
		M		M
bulkhead mounting housing, with 2 levers	<b>CHIN 10</b>			
surface mounting housing, high construction, with 2 levers	<b>MAPN 10.32</b>	<b>32</b>		
with pegs, side entry			<b>MHON 10.25</b>	<b>25</b>
with pegs, side entry, high construction			<b>MFON 10.32</b>	<b>32</b>
with pegs, top entry			<b>MHVN 10.25</b>	<b>25</b>
with pegs, top entry, high construction			<b>MFVN 10.32</b>	<b>32</b>

**\*\*) only in the CHIN 10 enclosure**

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder  
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm

**CHIN 10**

**MAPN 10.32**

dimensions in mm

**MFON 10.32**

**MFVN 10.32**

**MHON 10.25**

**MHVN 10.25**