


Part number

PE 16114 SA



Mobile plug, PLUSO series, 3 poles + PE, 11 h (red), 16 A, 440 ÷ 460 V, angled

Product description

Product type	Plug Mobile
Series	PE...SA, PLUSO
N. of poles	3 poles + 
Clock position	11
Specification	Angled

Technical data

Current	16 A
Voltage	440 ÷ 460 V
IP degree of protection	IP44

Further technical details

Weight	116,00 g
Operating temperature range (min, max)	-25°C ... +40°C

Material properties

Colour	RAL 7035 grey, RAL 3000 red
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade

Approvals / Standards

Reference standard	EN 60309-1 and -2
---------------------------	-------------------

General ordering information

EAN13 code	8015747062862
-------------------	---------------

Packaging Information

Sub-packaging length	140,00 mm
Sub-packaging height	135,00 mm
Sub-packaging width	235,00 mm
Sub-packaging weight	1,16 kg
Sub-packaging volume	4,44 dm ³
Sub-packaging description	Carton box
Sub-packaging quantity	10 Pcs
Sub-packaging EAN barcode	8015747062879

Part number

PE 16114 SA



Catalogue drawings

(16 / 32A) PE ... SA



PE...SA	A	B	C	Pg Ø
16A 2P+⊕	100	77	59	13,5
3P+⊕	100	84	68	16
3P+N+⊕	106	91	77	16
32A 2P+⊕	131	100	82	21
3P+⊕	131	100	82	21
3P+N+⊕	131	107	93	21