


Part number

PE 1643 PV



Mobile socket outlet, PLUSO series, 2 poles + PE, 4 h (yellow), 16 A, 100 ÷ 130 V

| Product description | | Material properties | |
|---|---|----------------------------------|--|
| Product type | Socket Mobile | Colour | RAL 7035 grey, RAL 1021 yellow |
| Series | PE...PV, PLUSO | RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| Connection type | Screw terminal connection | China RoHs - EFUP | 50 |
| N. of poles | 2 poles +  | REACH SVHC substances | Yes Lead |
| Clock position | 4 | SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |
| Technical data | | Approvals / Standards | |
| Current | 16 A | Reference standard | EN 60309-1 and -2 |
| Voltage | 100 ÷ 130 V | General ordering information | |
| IP degree of protection | IP44 | EAN13 code | 8015747063814 |
| Further technical details | | Packaging Information | |
| Weight | 135,00 g | Packaging length | 208,00 mm |
| Operating temperature range (min, max) | -25°C ... +40°C | Packaging height | 140,00 mm |
| | | Packaging width | 290,00 mm |
| | | Sub-packaging weight | 1,35 kg |
| | | Sub-packaging description | Carton box |
| | | Sub-packaging quantity | 10 Pcs |
| | | Sub-packaging EAN barcode | 8015747063821 |


Part number

PE 1643 PV



Catalogue drawings

(16 / 32A) PE ... PV



| PE...PV | A | B | Ø min | Ø max | |
|-----------------|--------|-------|-------|-------|----|
| 16A 2P+⊕ | 157,5 | 68 | 7 | 17 | |
| | 3P+⊕ | 164,5 | 76 | 7 | 17 |
| | 3P+N+⊕ | 183,5 | 83 | 9 | 22 |
| 32A 2P+⊕ | 200,5 | 87 | 9 | 22 | |
| | 3P+⊕ | 200,5 | 87 | 9 | 22 |
| | 3P+N+⊕ | 200,5 | 91 | 9 | 22 |