


Part number

PE 1663 SI



Flush-mounting plug, PLUSO series, 2 poles + PE, 6 h (blue), 16 A, 200 ÷ 250 V

| Product description | | Material properties | |
|---|---|------------------------------|---|
| Product type | Plug Flush-mounting | Colour | RAL 7035 grey, RAL 5015 blue |
| Series | PE...SI, PLUSO | RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 2 poles +  | China RoHs - EFUP | 50 |
| Clock position | 6 | REACH SVHC substances | Yes Lead |
| Size | Fixing centre distance socket 52 x 60 mm | SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |
| Technical data | | Approvals / Standards | |
| Current | 16 A | Reference standard | EN 60309-1 and -2 |
| Voltage | 200 ÷ 250 V | General ordering information | |
| IP degree of protection | IP44 | EAN13 code | 8015747064491 |
| Further technical details | | Packaging Information | |
| Weight | 113,00 g | Packaging length | 208,00 mm |
| Operating temperature range (min, max) | -25°C ... +40°C | Packaging height | 140,00 mm |
| | | Packaging width | 290,00 mm |
| | | Packaging weight | 1,33 kg |
| | | Packaging volume | 8,44 dm ³ |
| | | Packaging description | Carton box |
| | | Packaging quantity | 10 Pcs |
| | | Packaging EAN code | 8015747064507 |

Part number

PE 1663 SI



Catalogue drawings

(16 / 32A) PE ... SI



| PE ... SI | A | B | C | D | E | F | G | X | Y |
|-----------------|----|-----|-----|-----|----|----|------|----|----|
| 16A 2P+⊕ | 65 | 82 | 126 | 81 | 41 | 43 | 21,5 | 52 | 60 |
| | 65 | 82 | 126 | 81 | 47 | 43 | 21,5 | 52 | 60 |
| | 90 | 100 | 146 | 93 | 54 | 60 | 27,5 | 77 | 85 |
| 32A 2P+⊕ | 90 | 100 | 160 | 101 | 55 | 60 | 27,5 | 77 | 85 |
| | 90 | 100 | 160 | 101 | 55 | 60 | 27,5 | 77 | 85 |
| | 90 | 100 | 160 | 106 | 62 | 60 | 27,5 | 77 | 85 |