


Part number

# PEW 63114 PV



Mobile socket outlet, PLUSO series, 3 poles + PE, 11 h (red), 63 A, 440 ÷ 460 V

Product description		Material properties	
<b>Product type</b>	Socket Mobile	<b>Colour</b>	RAL 7035 grey, RAL 3000 red
<b>Series</b>	PEW...PV, PLUSO	<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	3 poles + 	<b>China RoHs - EFUP</b>	50
<b>Clock position</b>	11	<b>REACH SVHC substances</b>	Yes Lead
Technical data		<b>SCIP number</b>	Ca7de37f-add8-4b77-9861-279c94903ade
<b>Current</b>	63 A	Approvals / Standards	
<b>Voltage</b>	440 ÷ 460 V	<b>Reference standard</b>	EN 60309-1 and -2
<b>IP degree of protection</b>	IP67	General ordering information	
Further technical details		<b>EAN13 code</b>	8015747076531
<b>Weight</b>	915,00 g	Packaging Information	
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Packaging length</b>	300,00 mm
		<b>Packaging height</b>	130,00 mm
		<b>Packaging width</b>	200,00 mm
		<b>Packaging weight</b>	1,92 kg
		<b>Packaging volume</b>	7,80 dm <sup>3</sup>
		<b>Packaging description</b>	Carton box
		<b>Packaging quantity</b>	2 Pcs
		<b>Packaging EAN code</b>	8015747076548


Part number

# PEW 63114 PV



Catalogue drawings

(63 / 125A) PEW ... PV



PEW ... PV		A	B	Pg Ø
<b>63A</b>	2P+⊕	277	108,5	36
	3P+⊕	277	108,5	36
	3P+N+⊕	277	108,5	36
<b>125A</b>	2P+⊕	324	120,5	2" gas
	3P+⊕	324	120,5	2" gas
	3P+N+⊕	324	120,5	2" gas