

Part number

PK 12575 PB5



Interlocked switched socket-outlet, PK series,
3 poles + N + PE, 7 h (black), 125 A, 480 ÷
500 V, NH00 fuse carrier

| Product description | | Material properties | |
|--|------------------------------------|------------------------------|--|
| Product type | Interlocked switched socket-outlet | Colour | RAL 7035 grey, RAL 9005 black |
| Series | PK..PB5 | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 3 poles + N + | RoHs conformity | 50 |
| Clock position | 7 | China RoHs - EFUP | 50 |
| Specification | NH00 fuse carrier | REACH SVHC substances | Yes Lead |
| Technical data | | SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |
| Current | 125 A | Approvals / Standards | |
| Voltage | 480 ÷ 500 V | Reference standard | EN 60309-1, -2 e -4 |
| IP degree of protection | IP55 | General ordering information | |
| Further technical details | | EAN13 code | 8015747079549 |
| Weight | 9.200,00 g | Packaging Information | |
| Operating temperature range (min, max) | -25°C ... +40°C | Packaging length | 570,00 mm |
| IK rating (impact degree of protection) | IK10 | Packaging height | 200,00 mm |
| | | Packaging width | 265,00 mm |
| | | Packaging weight | 9,90 kg |
| | | Packaging volume | 30,21 dm ³ |
| | | Packaging description | Carton box |
| | | Packaging quantity | 1 Pcs |
| | | Packaging EAN code | 8015747079556 |
| | | Sub-packaging length | 113,00 mm |
| | | Sub-packaging height | 36,00 mm |
| | | Sub-packaging width | 180,00 mm |
| | | Sub-packaging volume | 0,73 dm ³ |

Part number

PK 12575 PB5



Catalogue drawings

