

Part number

PK 3275 EB



Interlocked switched socket-outlet, PK series,
3 poles + N + PE, 7 h (black), 32 A, 277/480 ÷
288/500 V, without fuse-carrier

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7035 grey, RAL 9005 black
Series	PK..EB		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + N +	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Clock position	7	China RoHs - EFUP	50
Cable entry	Pg29	REACH SVHC substances	Yes Lead
Specification	Without fuse-carrier	SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Technical data		Approvals / Standards	
Current	32 A	Reference standard	EN 60309-1, -2 e -4
Voltage	277/480 ÷ 288/500 V	General ordering information	
IP degree of protection	IP44	EAN13 code	8015747081818
Further technical details		Packaging Information	
Weight	1.330,00 g	Sub-packaging length	290,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Sub-packaging height	125,00 mm
IK rating (impact degree of protection)	IK10	Sub-packaging width	155,00 mm
		Sub-packaging weight	1,33 kg
		Sub-packaging volume	5,62 dm ³
		Sub-packaging description	Carton box
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747081825

Part number

PK 3275 EB



Catalogue drawings

