

Part number

PK 63114 EB



Interlocked switched socket-outlet, PK series, 3 poles + PE, 11 h (red), 63 A, 440 ÷ 460 V, without fuse-carrier

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7035 grey, RAL 3000 red
Series	PK..EB		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles +	RoHs conformity	50
Clock position	11	China RoHs - EFUP	Yes
Cable entry	Pg29	REACH SVHC substances	Lead
Specification	Without fuse-carrier	SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Technical data		Approvals / Standards	
Current	63 A	Reference standard	EN 60309-1, -2 e -4
Voltage	440 ÷ 460 V	General ordering information	
IP degree of protection	IP44	EAN13 code	8015747082129
Further technical details		Packaging Information	
Weight	1.650,00 g	Packaging length	535,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Packaging height	320,00 mm
IK rating (impact degree of protection)	IK10	Packaging width	325,00 mm
		Packaging weight	16,40 kg
		Packaging volume	55,64 dm ³
		Packaging description	Carton box
		Packaging quantity	8 Pcs
		Packaging EAN code	8015747082136
		Sub-packaging length	290,00 mm
		Sub-packaging height	125,00 mm
		Sub-packaging width	155,00 mm
		Sub-packaging weight	2,05 kg
		Sub-packaging volume	5,62 dm ³
		Sub-packaging description	Carton box
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747082143

Part number

PK 63114 EB



Catalogue drawings

