


Part number

PK 6344 EB



Interlocked switched socket-outlet, PK series,
3 poles + PE, 4 h (yellow), 63 A, 100 ÷ 130 V,
without fuse-carrier

| | | | |
|--|---|--------------------------------------|--|
| Product description | | Material properties | |
| Product type | Interlocked switched socket-outlet | Colour | RAL 7035 grey, RAL 1021 yellow |
| Series | PK..EB | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 3 poles +  | RoHs conformity | 6(c): copper alloy containing up to 4% lead by weight |
| Clock position | 4 | China RoHs - EFUP | 50 |
| Size | 114x228 fixing plates FC xx41 TB | REACH SVHC substances | Yes Lead |
| Cable entry | Pg29 | SCIP number | F6799547-ab84-42f2-938f-233ba663766d |
| Specification | Without fuse-carrier | Approvals / Standards | |
| Technical data | | Reference standard | EN 60309-1, -2 e -4 |
| Current | 63 A | General ordering information | |
| Voltage | 100 ÷ 130 V | EAN13 code | 8015747082259 |
| IP degree of protection | IP44 | Packaging Information | |
| Further technical details | | Sub-packaging length | 290,00 mm |
| Weight | 1.800,00 g | Sub-packaging height | 125,00 mm |
| Operating temperature range (min, max) | -25°C ... +40°C | Sub-packaging width | 155,00 mm |
| IK rating (impact degree of protection) | IK10 | Sub-packaging weight | 1,80 kg |
| | | Sub-packaging volume | 5,62 dm ³ |
| | | Sub-packaging description | Carton box |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747082266 |

Part number

PK 6344 EB



Catalogue drawings

