


Part number

RCEM 16



Male insert, RCE series, crimp connection, 16 poles + PE, 16 A 500 V 6 kV 3, size "77.27", HNM - High Number of Matings version

Product description

Product type	Insert
Series	RCE
Connection type	Crimp connection
Gender	Male
N. of poles	16 poles + 
Size	Size 77.27
Specification	HNM - High Number of Matings version

Technical data

Current	16 A
Voltage	500 V
Rated impulse withstand voltage	6 kV
Pollution degree	3
Rated voltage according to UL/CSA	600 V
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure

Further technical details

Mating cycles	≥ 10000
Insulation resistance	≥ 10 GΩ
Contact resistance	≤ 1 mΩ
Weight	0,33 g
Operating temperature range (min, max)	-40 °C ... +125 °C
UL 94 flammability rating	V-0

Material properties

Main material	Polycarbonate (PC)
Colour	RAL 7032 grey
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV, EAC
UL	ECBT2

General ordering information

EAN13 code	8015747253567
eCl@ss 8.1	27440205
ETIM 7.0	EC000438

Packaging Information


Packaging length	230,00 mm
Packaging height	110,00 mm
Packaging width	180,00 mm
Packaging volume	4,55 dm ³
Packaging description	Carton box
Packaging quantity	30 Pcs
Packaging EAN code	8015747253581
Sub-packaging length	87,00 mm
Sub-packaging height	36,00 mm
Sub-packaging width	180,00 mm
Sub-packaging volume	0,56 dm ³
Sub-packaging description	Carton tray
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747253598

Part number

RCEM 16



Catalogue drawings



Derating curves

