


Part number

TM 1635 IS



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 3 h (red), 16 A, 380 ÷ 380 V, sectionable fuse carrier 10 x 38 mm, with base box

Product description

| | |
|-----------------------|-------------------------------------------------------------------------------------------------|
| Product type | Interlocked switched socket-outlet |
| Series | TM.. IS/KIS |
| N. of poles | 3 poles + N +  |
| Clock position | 3 |
| Specification | Sectionable fuse carrier 10 x 38 mm With base box |

Technical data

| | |
|--------------------------------|---------------------------|
| Current | 16 A |
| Voltage | 380V (50Hz.) 440V (60Hz.) |
| IP degree of protection | IP66 / IP67 |

Further technical details

| | |
|------------------------------------------------|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|---------------|-----------------------------|
| Colour | RAL 7012 grey, RAL 3000 red |
|---------------|-----------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747161404 |
|-------------------|---------------|

Part number

TM 1635 IS



Catalogue drawings



| | A | B |
|---------------------------------|-----|-----|
| 2P+\oplus | 133 | 276 |
| 3P+\oplus | 135 | 276 |
| 3P+N+\oplus | 140 | 277 |