


Part number

TM 1674 SSP



Interlocked switched socket-outlet, TM series, 3 poles + PE, 7 h (black), 16 A, 480 ÷ 500 V, without fuse-carrier, without base box

| Product description | | Material properties | |
|--|---|----------------------------------|--|
| Product type | Interlocked switched socket-outlet | Colour | RAL 7012 grey, RAL 9005 black |
| Series | TM..SSP/KSSP | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 3 poles +  | RoHs conformity | 6(c): copper alloy containing up to 4% lead by weight |
| Clock position | 7 | China RoHs - EFUP | 50 |
| Specification | Without fuse-carrier Without base box | REACH SVHC substances | Yes Lead |
| Technical data | | SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |
| Current | 16 A | Approvals / Standards | |
| Voltage | 480 ÷ 500 V | Reference standard | EN 60309-1, -2 e -4 |
| IP degree of protection | IP66 / IP67 | General ordering information | |
| Further technical details | | EAN13 code | 8015747100953 |
| Weight | 1.045,00 g | Packaging Information | |
| Operating temperature range (min, max) | -25°C ... +40°C | Packaging weight | 10,00 kg |
| UL 94 flammability rating | V-2 | Packaging volume | 52,36 dm ³ |
| IK rating (impact degree of protection) | IK10 | Packaging description | Carton box |
| | | Packaging quantity | 9 Pcs |
| | | Packaging EAN code | 8015747035729 |
| | | Sub-packaging length | 95,00 mm |
| | | Sub-packaging height | 40,00 mm |
| | | Sub-packaging width | 253,00 mm |
| | | Sub-packaging weight | 1,11 kg |
| | | Sub-packaging volume | 0,96 dm ³ |
| | | Sub-packaging description | Plastic packaging |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747083461 |

Part number

TM 1674 SSP



Catalogue drawings



| | A | B |
|---------------|----------|----------|
| 2P+⊕ | 83 | 276 |
| 3P+⊕ | 85 | 276 |
| 3P+N+⊕ | 90 | 277 |