


Part number

# TM 32104 IS



Interlocked switched socket-outlet, TM series, 3 poles + PE, 10 h (green), 32 A, > 50 V, sectionable fuse carrier 14 x 51 mm, with base box

| Product description                            |   |
|--|---|
| <b>Product type</b>                            | Interlocked switched socket-outlet  |
| <b>Series</b>                                  | TM.. IS/KIS   |
| <b>N. of poles</b>                             | 3 poles +  |
| <b>Clock position</b>                          | 10  |
| <b>Specification</b>                           | Sectionable fuse carrier 14 x 51 mm<br>With base box  |
| Technical data                                 |   |
| <b>Current</b>                                 | 32 A  |
| <b>Voltage</b>                                 | > 50 V  |
| <b>IP degree of protection</b>                 | IP66 / IP67   |
| Further technical details                      |   |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C   |
| <b>UL 94 flammability rating</b>               | V-2   |
| <b>IK rating (impact degree of protection)</b> | IK10  |

| Material properties          |                               |
|------------------------------|-------------------------------|
| <b>Colour</b>                | RAL 7012 grey, RAL 6017 green |
| Approvals / Standards        |                               |
| <b>Reference standard</b>    | EN 60309-1, -2 e -4           |
| General ordering information |                               |
| <b>EAN13 code</b>            | 8015747161824                 |

Part number

# TM 32104 IS



Catalogue drawings



|               | <b>A</b> |
|---------------|----------|
| <b>2P+⊕</b>   | 162      |
| <b>3P+⊕</b>   | 162      |
| <b>3P+N+⊕</b> | 169      |