


Part number

TM 6345 IS



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 4 h (yellow), 63 A, 100 ÷ 130 V, sectionable fuse carrier 22 x 58 mm, with base box

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM.. IS/KIS |
| N. of poles | 3 poles + N +  |
| Clock position | 4 |
| Size | 145 x 565 x 18 mm |
| Specification | Sectionable fuse carrier 22 x 58 mm With base box |

Technical data

| | |
|--------------------------------|-------------|
| Current | 63 A |
| Voltage | 100 ÷ 130 V |
| IP degree of protection | IP66 / IP67 |

Further technical details

| | |
|--|-------------------------------|
| Weight | 4.320,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-0 (insert), V-2 (enclosure) |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|---------------|--------------------------------|
| Colour | RAL 7012 grey, RAL 1021 yellow |
|---------------|--------------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747092432 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|---------------|
| Sub-packaging weight | 4,32 kg |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747108850 |

Part number

TM 6345 IS



Catalogue drawings

