

Artikelnummer

MFVN 24.32



Tüllengehäuse, hoch, Gr.104.27, LS-TYPE Alu,
4 Bolzen, 1xM32 gerade, ohne Stutzen

Produktbeschreibung

Produkttyp	Tüllengehäuse
Baureihe	LS-TYPE
Verschlussystem	Mit 4 Bolzen
Größe	Größe 104.27
Kabelausgang	Gerader Kabelausgang M32
Spezifikationen	Hoch

Technische Daten

IP-Schutzart IP65

Weitere technische Details

Betriebstemperatur (min., max.) -40°C...+125°C

Materialeigenschaften

Farbe	RAL 9005 tiefschwarz
RoHs Konformität	Konform
China RoHs - EFUP	E
REACH SVHC Substanzen	Nein

Zulassungen / Standards

Zertifizierungen	DNV, BV
UL	ECBT2
c UL	ECBT8

Allgemeine Bestellinformationen

EAN-Code 13	8015747163606
Klassifizierung ecl@ss	27440202
Klassifizierung ETIM	EC000437

Angaben zur Verpackung

Beschreibung der Unterverpackung	Pack
Unterverpackungsmenge	5 St.
EAN-Code 13 Unterverpackung	8015747187824

Artikelnummer MFVN 24.32



Zeichnungen aus dem Katalog



Zeichnungen aus dem Katalog

CH..N - MA, MF..N enclosures size "104.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CD	64 poles + @ 51+53 *		
CT, CTS **)	64 poles + @ 57 *		
CDD	108 poles + @ 64+66 *		
CDE	46 poles + @ 83+85 *		
CSH	24 poles + @ 91+93 *		
CCE	24 poles + @ 100+104 *		
CNE, CSE, JCNE, JCSE	24 poles + @ 101 and 109 *		
CSS	24 poles + @ 122+123 *		
CTE, CTSE **)	24 poles + @ 129 *		
CMSE	10+2 (aux) poles + @ 139 *		
CMCE	10+2 (aux) poles + @ 138 *		
CX	4/8 poles + @ 155 *		
MIXO	6 modules 160+195 *		

insert centre distance: 104 x 27 mm
* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with 2 levers	CHIN 24	M		
surface mounting housing, high construction, with 2 levers	MAPN 24.32	32		
with pegs, side entry			MHON 24.32	32
with pegs, side entry, high construction			MFON 24.32	32
with pegs, side entry			MHVN 24.32	32
with pegs, side entry, high construction			MFVN 24.32	32

**) only in the CHIN 24 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm

CHIN 24

MAPN 24.32

dimensions in mm

MFON 24.32

MFVN 24.32

MHON 24.32

MHVN 24.32

Hinweise

Die angegebenen Abmessungen in mm sind nicht verbindlich.
Technische Änderungen bleiben vorbehalten.