

Artikelnummer

# MHON 06 L25




Tüllengehäuse, Gr.44.27, LS-TYPE Alu, 2  
Bolzen, 1xM25 seitlich

Produktbeschreibung		Materialeigenschaften	
<b>Produkttyp</b>	Tüllengehäuse	<b>Farbe</b>	RAL 9005 tiefschwarz
<b>Baureihe</b>	LS-TYPE	<b>RoHs Konformität</b>	Konform
<b>Verschlussystem</b>	Mit 2 Bolzen	<b>China RoHs - EFUP</b>	E
<b>Größe</b>	Größe "44.27"	<b>REACH SVHC Substanzen</b>	Nein
<b>Kabelausgang</b>	Seitlicher Kabelausgang M25	<b>Zulassungen / Standards</b>	
<b>Technische Daten</b>		<b>Zertifizierungen</b>	DNV, BV
<b>IP-Schutzart</b>	IP65	<b>UL</b>	ECBT2
<b>Weitere technische Details</b>		<b>c UL</b>	ECBT8
<b>Gewicht</b>	95,00 g	<b>Allgemeine Bestellinformationen</b>	
<b>Betriebstemperatur (min., max.)</b>	-40°C...+125°C	<b>EAN-Code 13</b>	8015747194181
		<b>Klassifizierung ecl@ss</b>	27440202
		<b>Klassifizierung ETIM</b>	EC000437
		<b>Angaben zur Verpackung</b>	
		<b>Gewicht der Unterverpackung</b>	0,48 kg
		<b>Beschreibung der Unterverpackung</b>	Pack
		<b>Unterverpackungsmenge</b>	5 St.
		<b>EAN-Code 13 Unterverpackung</b>	8015747194198

# Artikelnummer MHON 06 L25



Zeichnungen aus dem Katalog



Zeichnungen aus dem Katalog

**CH..N - MA, MF..N enclosures** size "44.27" **LS-TYPE version**

inserts:	page	housings with single lever	hoods with 2 pegs
CDD .....	24 poles + ⊕ 59 *		
CQE .....	10 poles + ⊕ 80 *		
CSH .....	6 poles + ⊕ 88 *		
CCE .....	6 poles + ⊕ 94 *		
CNE, CSE, JONE, JCSE .....	6 poles + ⊕ 95 and 103 *		
CSS .....	6 poles + ⊕ 118 *		
CTE, CTSE **) .....	6 poles + ⊕ 126 *		
MIXO .....	2 modules 160+195 *		

insert centre distance: 44 x 27 mm  
\* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with lever	<b>CHIN 06 L</b>	M		
surface mounting housing, high construction, with lever	<b>MAPN 06 L32</b>	<b>32</b>		
with pegs, side entry			<b>MHON 06 L25</b>	<b>25</b>
with pegs, side entry, high construction			<b>MFON 06 L25</b>	<b>25</b>
with pegs, top entry			<b>MHVN 06 L25</b>	<b>25</b>
with pegs, top entry, high construction			<b>MFVN 06 L25</b>	<b>25</b>

\*\*) only in the CHIN 06 L enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder  
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

IP65

dimensions shown are not binding and may be changed without notice

**4**

## Hinweise

Die angegebenen Abmessungen in mm sind nicht verbindlich.  
Technische Änderungen bleiben vorbehalten.