


Artikelnummer

# TM 32123KIS



#### Produktbeschreibung

<b>Produkttyp</b>	Steckdose mit Verriegelung
<b>Baureihe</b>	TM.. IS/KIS
<b>Polzahl</b>	2 polig + 
<b>Position des Schutzleiters</b>	12
<b>Spezifikationen</b>	Verriegelbarer Inspektionsklappe 10 x 38 mm Mit Einzelgehäuse

#### Technische Daten

<b>Strom</b>	32 A
<b>Spannung</b>	ins. transformer
<b>IP-Schutzart</b>	IP66 / IP67

#### Weitere technische Details

<b>Betriebstemperatur (min., max.)</b>	-25°C ... +40°C
<b>Selbstverlöschungsgrad UL 94</b>	V-2
<b>IK-Schutzart</b>	IK10

#### Materialeigenschaften

<b>Farbe</b>	RAL 7012 basaltgrau, RAL 9010 reinweiß
--------------	--

#### Zulassungen / Standards

<b>Bezugsnorm</b>	EN 60309-1, -2 e -4
-------------------	---------------------

#### Allgemeine Bestellinformationen

<b>EAN-Code 13</b>	8015747162173
--------------------	---------------

# Artikelnummer TM 32123KIS



Zeichnungen aus dem Katalog

### TM.. IS/KIS interlocked socket-outlets and sectionable fuse carrier

- Compliant with EN 60309 -1, -2 and 4
- Enclosures in insulating self-extinguishing thermoplastic material, RAL 7012 grey
- Mechanical resistance to impacts: 20 J (IK 10 as EN 50102)
- Socket-outlets with bayonet fastening cover
- Factory installed internal wiring
- Cable entry with drilling template
- "Zeta" switch with  $I_{n1} = 32A$  rating for 16A and 32A socket-outlets
- Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
- Knob lockable in positions 0 and 1
- Compartment with sectionable fuse carrier (fuses not supplied) and inspection panel openable only when the switch is off
- With Italian Quality Mark

Rated current socket part	Maximum operating current	Fuse carrier CH type
16A	16A	10 x 38
32A	32A	10 x 38

**16A**  
IP66/IP67 degree of protection

**32A**  
IP66/IP67 degree of protection

Poles	Frequency Hz	Voltage V	Earthing contact position h	Part No.	Colour	Part No.	Colour	
2P+Ⓢ	50 and 60	100 - 130	4	TM 1643 IS Ⓢ	Yellow	TM 3243KIS Ⓢ	Yellow	
	50 and 60	200 - 250	6	TM 1663 IS Ⓢ	Blue	TM 3263KIS Ⓢ	Blue	
	50 and 60	380 - 415	9	TM 1693 IS Ⓢ	Red	TM 3293KIS Ⓢ	Red	
	50 and 60	480 - 500	7	TM 1673 IS Ⓢ	Black	TM 3273KIS Ⓢ	Black	
	50 and 60	ins. transformer	12	TM 16123 IS Ⓢ	A.V.	TM 32123KIS Ⓢ	A.V.	
	> 300 - 500	> 50	2	TM 1623 IS Ⓢ	Green	TM 3223KIS Ⓢ (up to 400V)	Green	
	> 300 - 500	> 50 - 250	3	TM 1633 IS Ⓢ	A.V.	TM 3233KIS Ⓢ	A.V.	
	3P+Ⓢ	50 and 60	100 - 130	4	TM 1644 IS Ⓢ	Yellow	TM 3244KIS Ⓢ	Yellow
		50 and 60	200 - 250	9	TM 1694 IS Ⓢ	Blue	TM 3294KIS Ⓢ	Blue
		50 and 60	380 - 415	6	TM 1664 IS Ⓢ	Red	TM 3264KIS Ⓢ	Red
60		440 - 460	11	TM 16114 IS Ⓢ	Black	TM 32114KIS Ⓢ	Black	
50 and 60		480 - 500	7	TM 1674 IS Ⓢ	Black	TM 3274KIS Ⓢ	Black	
50		380	3	TM 1634 IS Ⓢ	Red	TM 3234KIS Ⓢ	Red	
60		440	3	TM 1634 IS Ⓢ	Red	TM 3234KIS Ⓢ	Red	
100 - 300		> 50	10	TM 16104 IS Ⓢ	Green	TM 32104KIS Ⓢ (up to 400V)	Green	
> 300 - 500		> 50	2	TM 1624 IS Ⓢ	Green	TM 3224KIS Ⓢ (up to 400V)	Green	
3P+N+Ⓢ		50 and 60	57/100 - 75/130	4	TM 1645 IS Ⓢ	Yellow	TM 3245KIS Ⓢ	Yellow
	50 and 60	120/208 - 144/250	9	TM 1695 IS Ⓢ	Blue	TM 3295KIS Ⓢ	Blue	
	50 and 60	200/346 - 240/415	6	TM 1665 IS Ⓢ	Red	TM 3265KIS Ⓢ	Red	
	50 and 60	277/480 - 288/500	7	TM 1675 IS Ⓢ	Black	TM 3275KIS Ⓢ	Black	
	60	250/440 - 265/460	11	TM 16115 IS Ⓢ	Black	TM 32115KIS Ⓢ	Black	
	50	220/380	3	TM 1635 IS Ⓢ	Red	TM 3235KIS Ⓢ	Red	
	60	250/440	3	TM 1635 IS Ⓢ	Red	TM 3235KIS Ⓢ	Red	
	> 300 - 500	> 50	2	TM 1625 IS Ⓢ	Green	TM 3225KIS Ⓢ (up to 400V)	Green	

**Legend**  
A.V. = Colour according to voltage  
\*) Green may be used together with the colour of the operating range for frequencies above 60 Hz and up to a maximum of 500 Hz

**Accessories for socket-outlet combinations**

TM 1145 TB (page 24) with 1 plate  
TM 1114 DB (page 26) with 2 plates  
TM 1114 GB (page 27)

**Accessories for assembly on control panels**  
QP V - QG V

page 31

Dimensions indicated are not binding and may be changed without prior notice.

dimensions in mm

Poles	A	B
2P+Ⓢ	133	276
3P+Ⓢ	135	276
3P+N+Ⓢ	140	277

dimensions in mm

Poles	A
2P+Ⓢ	146
3P+Ⓢ	146
3P+N+Ⓢ	151

12

## Hinweise

Die angegebenen Abmessungen in mm sind nicht verbindlich.  
Technische Änderungen bleiben vorbehalten.