


Artikelnummer

# TM 3245KIS



## Produktbeschreibung

<b>Produkttyp</b>	Steckdose mit Verriegelung
<b>Baureihe</b>	TM.. IS/KIS
<b>Polzahl</b>	3 polig + neutro + 
<b>Position des Schutzleiters</b>	4
<b>Größe</b>	115 x 450 x 18 mm
<b>Spezifikationen</b>	Verriegelbarer Inspektionsklappe 10 x 38 mm Mit Einzelgehäuse

## Technische Daten

<b>Strom</b>	32 A
<b>Spannung</b>	57/100 + 75/130 V
<b>IP-Schutzart</b>	IP66 / IP67

## Weitere technische Details

<b>Gewicht</b>	1.695,00 g
<b>Betriebstemperatur (min., max.)</b>	-25°C ... +40°C
<b>Selbstverlöschunggrad UL 94</b>	V-2
<b>IK-Schutzart</b>	IK10

## Materialeigenschaften

<b>Farbe</b>	RAL 7012 basaltgrau, RAL 1021 rapsgelb
<b>RoHs Konformität</b>	Konform mit Ausnahme 6(c): Kupferlegierung mit einem Massenanteil von bis zu 4 % Blei
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC Substanzen</b>	Ja Blei
<b>SCIP Nummer</b>	Ce861c8d-b979-403b-96d9-80aef6dc281d

## Zulassungen / Standards

<b>Bezugsnorm</b>	EN 60309-1, -2 e -4
-------------------	---------------------

## Allgemeine Bestellinformationen

<b>EAN-Code 13</b>	8015747126564
--------------------	---------------

## Angaben zur Verpackung

<b>Länge der Verpackung</b>	385,00 mm
<b>Höhe der Verpackung</b>	320,00 mm
<b>Tiefe der Verpackung</b>	485,00 mm
<b>Gewicht der Verpackung</b>	15,81 kg
<b>Volumen der Verpackung</b>	59,75 dm <sup>3</sup>
<b>Beschreibung der Verpackung</b>	Karton
<b>Verpackungsmenge</b>	9 St.
<b>EAN-Code 13 Verpackung</b>	8015747202411
<b>Gewicht der Unterverpackung</b>	1,76 kg
<b>Beschreibung der Unterverpackung</b>	Pack
<b>Unterverpackungsmenge</b>	1 St.
<b>EAN-Code 13 Unterverpackung</b>	8015747202428

# Artikelnummer TM 3245KIS



Zeichnungen aus dem Katalog

### TM. IS/KIS interlocked socket-outlets and sectionable fuse carrier ILME

- Compliant with EN 60309 -1, -2 and 4
- Enclosures in insulating self-extinguishing thermoplastic material, RAL 7012 grey
- Mechanical resistance to impacts: 20 J (K 10 as EN 50102)
- Socket-outlets with bayonet fastening cover
- Factory installed internal wiring
- Cable entry with drilling template
- "Zeta" switch with  $I_{n1} = 32A$  rating for 16A and 32A socket-outlets
- Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
- Knob lockable in positions 0 and 1
- Compartment with sectionable fuse carrier (fuses not supplied) and inspection panel openable only when the switch is off
- With Italian Quality Mark

Rated current socket part	Maximum operating current	Fuse carrier CH type
16A	16A	10 x 38
32A	32A	10 x 38

Poles	Frequency Hz	Voltage V	Earthing contact position h	Part No.	Colour	Part No.	Colour	
2P+Ⓢ	50 and 60	100 - 130	4	TM 1643 IS Ⓢ	Yellow	TM 3243KIS Ⓢ	Yellow	
		200 - 250	6	TM 1663 IS Ⓢ	Blue	TM 3263KIS Ⓢ	Blue	
	50 and 60	380 - 415	9	TM 1693 IS Ⓢ	Red	TM 3293KIS Ⓢ	Red	
		480 - 500	7	TM 1673 IS Ⓢ	Black	TM 3273KIS Ⓢ	Black	
	50 and 60	ins. transformer	12	TM 16123 IS Ⓢ	A.V.	TM 32123KIS Ⓢ	A.V.	
			2	TM 1623 IS Ⓢ	+	TM 3223KIS Ⓢ (up to 400V)	+	
	> 300 - 500	> 50 - 250	3	TM 1633 IS Ⓢ	A.V.	TM 3233KIS Ⓢ	A.V.	
			3	TM 1633 IS Ⓢ	A.V.	TM 3233KIS Ⓢ	A.V.	
	3P+Ⓢ	50 and 60	100 - 130	4	TM 1644 IS Ⓢ	Yellow	TM 3244KIS Ⓢ	Yellow
			200 - 250	9	TM 1694 IS Ⓢ	Red	TM 3294KIS Ⓢ	Red
50 and 60		380 - 415	6	TM 1664 IS Ⓢ	Blue	TM 3264KIS Ⓢ	Blue	
		440 - 460	11	TM 16114 IS Ⓢ	Black	TM 32114KIS Ⓢ	Black	
50 and 60		480 - 500	7	TM 1674 IS Ⓢ	Black	TM 3274KIS Ⓢ	Black	
			3	TM 1634 IS Ⓢ	Black	TM 3234KIS Ⓢ	Black	
60		440	3	TM 1634 IS Ⓢ	Black	TM 3234KIS Ⓢ	Black	
			3	TM 1634 IS Ⓢ	Black	TM 3234KIS Ⓢ	Black	
100 - 300		> 50	10	TM 16104 IS Ⓢ	*	TM 32104KIS Ⓢ (up to 400V)	*	
			2	TM 1624 IS Ⓢ	*	TM 3224KIS Ⓢ (up to 400V)	*	
> 300 - 500	> 50	10	TM 16104 IS Ⓢ	*	TM 32104KIS Ⓢ (up to 400V)	*		
		2	TM 1624 IS Ⓢ	*	TM 3224KIS Ⓢ (up to 400V)	*		
3P+N+Ⓢ	50 and 60	57/100 - 75/130	4	TM 1645 IS Ⓢ	Yellow	TM 3245KIS Ⓢ	Yellow	
		120/208 - 144/250	9	TM 1695 IS Ⓢ	Red	TM 3295KIS Ⓢ	Red	
	50 and 60	200/346 - 240/415	6	TM 1665 IS Ⓢ	Blue	TM 3265KIS Ⓢ	Blue	
			7	TM 1675 IS Ⓢ	Black	TM 3275KIS Ⓢ	Black	
	60	250/440 - 265/460	11	TM 16115 IS Ⓢ	Black	TM 32115KIS Ⓢ	Black	
			3	TM 1635 IS Ⓢ	Black	TM 3235KIS Ⓢ	Black	
	50	220/380	3	TM 1635 IS Ⓢ	Black	TM 3235KIS Ⓢ	Black	
3			TM 1635 IS Ⓢ	Black	TM 3235KIS Ⓢ	Black		
> 300 - 500	> 50	2	TM 1625 IS Ⓢ	*	TM 3225KIS Ⓢ (up to 400V)	*		
		2	TM 1625 IS Ⓢ	*	TM 3225KIS Ⓢ (up to 400V)	*		

**Legend**  
A.V. = Colour according to voltage  
\*) Green may be used together with the colour of the operating range for frequencies above 60 Hz and up to a maximum of 500 Hz

**Accessories for socket-outlet combinations**

**Accessories for assembly on control panels**  
QP V - QG V

page 31

Dimensions indicated are not binding and may be changed without prior notice.

dimensions in mm

Poles	A	B
2P+Ⓢ	133	276
3P+Ⓢ	135	276
3P+N+Ⓢ	140	277

dimensions in mm

Poles	A
2P+Ⓢ	146
3P+Ⓢ	146
3P+N+Ⓢ	151

## Hinweise

Die angegebenen Abmessungen in mm sind nicht verbindlich.  
Technische Änderungen bleiben vorbehalten.