


Artikelnummer
TM 3294KIS



Produktbeschreibung

| | |
|-----------------------------------|---|
| Produkttyp | Steckdose mit Verriegelung |
| Baureihe | TM.. IS/KIS |
| Polzahl | 3 polig +  |
| Position des Schutzleiters | 9 |
| Größe | 115 x 450 x 18 mm |
| Spezifikationen | Verriegelbarer Inspektionsklappe 10 x 38 mm Mit Einzelgehäuse |

Technische Daten

| | |
|---------------------|-------------|
| Strom | 32 A |
| Spannung | 200 ÷ 250 V |
| IP-Schutzart | IP66 / IP67 |

Weitere technische Details

| | |
|--|-----------------|
| Gewicht | 1.660,00 g |
| Betriebstemperatur (min., max.) | -25°C ... +40°C |
| Selbstverlöschunggrad UL 94 | V-2 |
| IK-Schutzart | IK10 |

Materialeigenschaften

| | |
|--------------|--|
| Farbe | RAL 7035 basaltgrau, RAL 5015 himmelblau |
|--------------|--|

Zulassungen / Standards

| | |
|-------------------|---------------------|
| Bezugsnorm | EN 60309-1, -2 e -4 |
|-------------------|---------------------|

Allgemeine Bestellinformationen

| | |
|--------------------|---------------|
| EAN-Code 13 | 8015747126267 |
|--------------------|---------------|

Artikelnummer TM 3294KIS



Zeichnungen aus dem Katalog

TM.. IS/KIS interlocked socket-outlets and sectionable fuse carrier

- Compliant with EN 60309 -1, -2 and 4
- Enclosures in insulating self-extinguishing thermoplastic material, RAL 7012 grey
- Mechanical resistance to impacts: 20 J (K 10 as EN 50102)
- Socket-outlets with bayonet fastening cover
- Factory installed internal wiring
- Cable entry with drilling template
- "Zeta" switch with I_{n1} = 32A rating for 16A and 32A socket-outlets
- Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
- Knob lockable in positions 0 and 1
- Compartment with sectionable fuse carrier (fuses not supplied) and inspection panel openable only when the switch is off
- With Italian Quality Mark

| Rated current socket part | Maximum operating current | Fuse carrier CH type |
|---------------------------|---------------------------|----------------------|
| 16A | 16A | 10 x 38 |
| 32A | 32A | 10 x 38 |

16A
IP66/IP67 degree of protection

32A
IP66/IP67 degree of protection

| Poles | Frequency Hz | Voltage V | Earthing contact position h | Part No. | Colour | Part No. | Colour | |
|-------------|--------------|-------------------|-----------------------------|---------------|--------------|----------------------------|--------------|--------|
| 2P+Ⓢ | 50 and 60 | 100 - 130 | 4 | TM 1643 IS Ⓢ | Yellow | TM 3243KIS Ⓢ | Yellow | |
| | 50 and 60 | 200 - 250 | 6 | TM 1663 IS Ⓢ | Blue | TM 3263KIS Ⓢ | Blue | |
| | 50 and 60 | 380 - 415 | 9 | TM 1693 IS Ⓢ | Red | TM 3293KIS Ⓢ | Red | |
| | 50 and 60 | 480 - 500 | 7 | TM 1673 IS Ⓢ | Black | TM 3273KIS Ⓢ | Black | |
| | 50 and 60 | ins. transformer | 12 | TM 16123 IS Ⓢ | A.V. | TM 32123KIS Ⓢ | A.V. | |
| | > 300 - 500 | > 50 | 2 | TM 1623 IS Ⓢ | Green | TM 3223KIS Ⓢ (up to 400V) | Green | |
| | > 300 - 500 | > 50 - 250 | 3 | TM 1633 IS Ⓢ | A.V. | TM 3233KIS Ⓢ | A.V. | |
| | 3P+Ⓢ | 50 and 60 | 100 - 130 | 4 | TM 1644 IS Ⓢ | Yellow | TM 3244KIS Ⓢ | Yellow |
| | | 50 and 60 | 200 - 250 | 9 | TM 1694 IS Ⓢ | Blue | TM 3294KIS Ⓢ | Blue |
| | | 50 and 60 | 380 - 415 | 6 | TM 1664 IS Ⓢ | Red | TM 3264KIS Ⓢ | Red |
| 60 | | 440 - 460 | 11 | TM 16114 IS Ⓢ | Black | TM 32114KIS Ⓢ | Black | |
| 50 and 60 | | 480 - 500 | 7 | TM 1674 IS Ⓢ | Black | TM 3274KIS Ⓢ | Black | |
| 50 | | 380 | 3 | TM 1634 IS Ⓢ | Green | TM 3234KIS Ⓢ | Green | |
| 60 | | 440 | 3 | TM 1634 IS Ⓢ | Green | TM 3234KIS Ⓢ | Green | |
| 100 - 300 | | > 50 | 10 | TM 16104 IS Ⓢ | Green | TM 32104KIS Ⓢ (up to 400V) | Green | |
| > 300 - 500 | | > 50 | 2 | TM 1624 IS Ⓢ | Green | TM 3224KIS Ⓢ (up to 400V) | Green | |
| 3P+N+Ⓢ | | 50 and 60 | 57/100 - 75/130 | 4 | TM 1645 IS Ⓢ | Yellow | TM 3245KIS Ⓢ | Yellow |
| | 50 and 60 | 120/208 - 144/250 | 9 | TM 1695 IS Ⓢ | Blue | TM 3295KIS Ⓢ | Blue | |
| | 50 and 60 | 200/346 - 240/415 | 6 | TM 1665 IS Ⓢ | Red | TM 3265KIS Ⓢ | Red | |
| | 50 and 60 | 277/480 - 288/500 | 7 | TM 1675 IS Ⓢ | Black | TM 3275KIS Ⓢ | Black | |
| | 60 | 250/440 - 265/460 | 11 | TM 16115 IS Ⓢ | Black | TM 32115KIS Ⓢ | Black | |
| | 50 | 220/380 | 3 | TM 1635 IS Ⓢ | Green | TM 3235KIS Ⓢ | Green | |
| | 60 | 250/440 | 3 | TM 1635 IS Ⓢ | Green | TM 3235KIS Ⓢ | Green | |
| | > 300 - 500 | > 50 | 2 | TM 1625 IS Ⓢ | Green | TM 3225KIS Ⓢ (up to 400V) | Green | |

Legend
A.V. = Colour according to voltage
*) Green may be used together with the colour of the operating range for frequencies above 60 Hz and up to a maximum of 500 Hz

Accessories for socket-outlet combinations

Accessories for assembly on control panels
QP V - QG V

page 31

Dimensions indicated are not binding and may be changed without prior notice.

dimensions in mm

| Poles | A | B |
|--------|-----|-----|
| 2P+Ⓢ | 133 | 276 |
| 3P+Ⓢ | 135 | 276 |
| 3P+N+Ⓢ | 140 | 277 |

dimensions in mm

| Poles | A |
|--------|-----|
| 2P+Ⓢ | 146 |
| 3P+Ⓢ | 146 |
| 3P+N+Ⓢ | 151 |

Hinweise

Die angegebenen Abmessungen in mm sind nicht verbindlich.
Technische Änderungen bleiben vorbehalten.