


Part number

BK 16115



Interlocked switched socket-outlet, BK series, 3 poles + N + PE, 11 h (red), 16 A, 250/440 ÷ 265/460 V, sectionable fuse carrier 10 x 38 mm

Product description

| | |
|-----------------------|-------------------------------------------------------------------------------------------------|
| Product type | Interlocked switched socket-outlet |
| Series | BK |
| N. of poles | 3 poles + N +  |
| Clock position | 11 |
| Specification | Sectionable fuse carrier 10 x 38 mm |

Technical data

| | |
|--------------------------------|---------------------|
| Current | 16 A |
| Voltage | 250/440V ÷ 265/460V |
| IP degree of protection | IP67 |

Further technical details

| | |
|------------------------------------------------|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|---------------|-----------------------------|
| Colour | RAL 7035 grey, RAL 3000 red |
|---------------|-----------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747147088 |
|-------------------|---------------|

Part number

BK 16115



Catalogue drawings



| BK | | A | B |
|-----|------------|-----|----|
| 16A | 2P + ⊕ | 105 | 50 |
| | 3P + ⊕ | 105 | 50 |
| | 3P + N + ⊕ | 110 | 50 |
| 32A | 2P + ⊕ | 140 | 58 |
| | 3P + ⊕ | 140 | 58 |
| | 3P + N + ⊕ | 140 | 58 |

Notes

Dimensions shown in mm are not binding and may be changed without notice.
