

Part number

CKSF 03



Female insert, CKS series, spring terminal connection, 3 poles + PE, 10 A 400 V 4 kV 3, size "21.21"



| Product description | |
|---|---|
| Product type | Insert |
| Series | CKS |
| Connection type | Spring terminal connection |
| Gender | Female |
| N. of poles | 3 poles + \oplus |
| Size | Size "21.21" |
| Technical data | |
| Current | 10 A |
| Voltage | 400 V |
| Rated impulse withstand voltage | 4 kV |
| Pollution degree | 3 |
| Rated voltage according to UL/CSA | 600 V |
| Wire cross-section | 0,14 mm ² - 2,50 mm ² |
| AWG size | 26 - 14 |
| Contact type | Turned silver plated |
| IP degree of protection | IP20 without enclosure, IP44/IP66/IP67/IP68/IP69 with enclosure |
| Further technical details | |
| Characteristics according to EN 61984 | 10A 400V 4kV 3; 10A 690V 4kV 2 |
| Mating cycles | ≥ 500 |
| Insulation resistance | ≥ 10 GΩ |
| Contact resistance | ≤ 3 mΩ |
| Weight | 15,00 g |
| Operating temperature range (min, max) | -40 °C ... +125 °C |
| Conductors stripping length | 9...11 mm |
| UL 94 flammability rating | V-0 |
| Torque for main contact | M2,5: 0.4 Nm; 3.5 lb.in (0,5 x 3mm) |
| Tightening torque for PE connection | M4: 1,2 Nm, 10,6 lb.in (Ph2 or 1,0x5,5mm) |
| Tightening torque for fixing screws | M3: 0,5 Nm; 4,4 lb.in (Ph1 or 0,8 x 5,5 mm) |

| Material properties | |
|----------------------------------|--|
| Main material | Polycarbonate (PC) |
| Other materials | Contacts: copper alloy |
| Colour | RAL 7032 grey |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | 1a9c93ff-0445-4a16-81e3-1609ac5274d6 |
| Approvals / Standards | |
| Reference standard | EN 61984:2009-06 |
| Certifications | CSA, CQC, DNV, BV, EAC |
| UL | ECBT2 |
| cUL | ECBT8 |
| General ordering information | |
| EAN13 code | 8015747164399 |
| ETIM 7.0 | ECC00438 |
| Packaging Information | |
| Packaging length | 210,00 mm |
| Packaging height | 200,00 mm |
| Packaging width | 130,00 mm |
| Packaging weight | 3,18 kg |
| Packaging volume | 5,46 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 200 Pcs |
| Packaging EAN code | 8015747164474 |
| Sub-packaging length | 197,00 mm |
| Sub-packaging height | 35,00 mm |
| Sub-packaging width | 113,00 mm |
| Sub-packaging weight | 0,64 kg |
| Sub-packaging volume | 0,78 dm ³ |
| Sub-packaging description | Carton tray |
| Sub-packaging quantity | 40 Pcs |
| Sub-packaging EAN barcode | 8015747164481 |


Part number
CKSF 03



Catalogue drawings




Catalogue drawings



Notes

Dimensions shown in mm are not binding and may be changed without notice.

Spring terminal connections



Rear top entry of wires for a more easier wiring.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.
