

Part number

# CW 10 SC9



Male fibre optic connector, CW SC patch cords series, GL fibre E9/125, yellow, 10 m cable, for single-module fibre

Product description	
Technical data	
<b>IP degree of protection</b>	IP20
Further technical details	
<b>Weight</b>	157,50 g
<b>Operating temperature range (min, max)</b>	-5 °C ... +55 °C

Material properties	
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	8b60cf05-8f5f-42af-80f1-e79cea373159
General ordering information	
<b>EAN13 code</b>	8015747032513
<b>eCl@ss 8.1</b>	27061003
<b>ETIM 7.0</b>	EC001263
Packaging Information	
<b>Sub-packaging weight</b>	0,16 kg
<b>Sub-packaging description</b>	Plastic bag
<b>Sub-packaging quantity</b>	1 Pcs
<b>Sub-packaging EAN barcode</b>	8015747033268

Part number

# CW 10 SC9



---

## Notes

Fiber type: single-mode, polished-terminated (PC)

Fiber designation: OS2

Attenuation: < 0,4 dB/km

Insertion loss:  $\leq 0,25$  dB

Return loss:  $\geq 45$  dB

Fiber height:  $-50 \div +50$  nm

---

Cable diameter:  $2 \times \varnothing 2,8$  mm

Relative humidity: 95 %

Apex offset:  $\leq 50$   $\mu$ m

Radius: 5 to 25 mm

---