

Part number

CW 2 SC50



Male fibre optic connector, CW SC patch cords series, GL fibre G50/125, orange, 2 m cable, for multi-module fibres

Product description

Technical data

IP degree of protection IP20

Further technical details

Operating temperature range (min, max) -5 °C ... +55 °C

Material properties

RoHs conformity Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight

China RoHs - EFUP 50

REACH SVHC substances Yes
Lead

SCIP number 8b60cf05-8f5f-42af-80f1-e79cea373159

General ordering information

EAN13 code 8015747032537

eCl@ss 8.1 27061003

ETIM 7.0 EC001263

Packaging Information

Sub-packaging description Plastic bag

Sub-packaging quantity 1 Pcs

Sub-packaging EAN barcode 8015747033275

Part number

CW 2 SC50



Notes

Fiber type: multi-mode, graded index (GI), polished-terminated (PC)

Fiber designation: OM2

Insertion loss: $\leq 0,25$ dB

Return loss: ≥ 40 dB

Fiber hight: $-50 \div +100$ nm

Cable diameter: $2 \times \varnothing 2,8$ mm

Relative humidity: 95 %

Apex offset: ≤ 50 μ m

Radius: 5 to 25 mm
