

Part number

CW 2 SC62



Male fibre optic connector, CW SC patch cords series, GL fibre G62,5/125, orange, 2 m cable, for multi-module fibres

Product description	
Technical data	
IP degree of protection	IP20
Further technical details	
Operating temperature range (min, max)	-5 °C ... +55 °C

Material properties	
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	8b60cf05-8f5f-42af-80f1-e79cea373159
General ordering information	
EAN13 code	8015747032735
eCl@ss 8.1	27061003
ETIM 7.0	EC001263
Packaging Information	
Sub-packaging description	Plastic bag
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747033282

Part number

CW 2 SC62



Notes

Fiber type: multi-mode, graded index (GI), polished-terminated (PC)

Fiber designation: OM1

Insertion loss: $\leq 0,25$ dB

Return loss: ≥ 40 dB

Fiber hight: $-50 \div +100$ nm

Cable diameter: $2 \times \varnothing 2,8$ mm

Relative humidity: 95 %

Apex offset: ≤ 50 μ m

Radius: 5 to 25 mm
