

Part number

# CX 02 JF



Female modular insert, Mixo Data series, RJ45, 3 modules, without connector, for 2 RJ45 connectors and 8 10 A CD contacts

#### Product description

<b>Product type</b>	Modular insert
<b>Series</b>	Mixo Data
<b>Connection type</b>	RJ45
<b>Gender</b>	Female
<b>N. of poles</b>	1 seat for RJ45 connector
<b>Auxiliary poles</b>	8 poles
<b>Size</b>	3 modules
<b>Specification</b>	For 2 RJ45 connectors and 8 10 A CD contacts RJ45, adapter for Cat. 6A female connector

#### Technical data

<b>Current</b>	1 A
<b>Voltage</b>	50 V
<b>Rated voltage according to UL/CSA</b>	600V
<b>IP degree of protection</b>	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure

#### Further technical details

<b>Characteristics according to EN 61984</b>	10A 250V 4kV 3
<b>Insulation resistance</b>	≥ 10 GΩ
<b>Contact resistance</b>	≤ 3 mΩ
<b>Weight</b>	18,00 g
<b>Operating temperature range (min, max)</b>	-40°C ... +120°C
<b>UL 94 flammability rating</b>	V-0

#### Material properties

<b>Main material</b>	Polycarbonate (PC)
<b>Colour</b>	RAL 7032 grey
<b>RoHs conformity</b>	Compliant
<b>China RoHs - EFUP</b>	E
<b>REACH SVHC substances</b>	No

#### Approvals / Standards

<b>Reference standard</b>	EN 61984:2009-06
<b>Certifications</b>	CSA, CQC, DNV, BV, EAC
<b>UL</b>	ECBT2
<b>cUL</b>	ECBT8

#### General ordering information

<b>EAN13 code</b>	8015747166027
<b>eCl@ss 8.1</b>	27440205
<b>ETIM 7.0</b>	EC000438

#### Packaging Information


<b>Sub-packaging length</b>	195,00 mm
<b>Sub-packaging height</b>	40,00 mm
<b>Sub-packaging width</b>	60,00 mm
<b>Sub-packaging weight</b>	0,14 kg
<b>Sub-packaging volume</b>	0,47 dm <sup>3</sup>
<b>Sub-packaging description</b>	Carton tray
<b>Sub-packaging quantity</b>	8 Pcs
<b>Sub-packaging EAN barcode</b>	8015747104074

Part number

# CX 02 JF



Catalogue drawings



## Notes

Standard modular inserts:

-in combination with standard contacts and standard frames (CX ... TF/TM); must be mounted either in traditional enclosures or in COB panel supports (both up to 500 matings).

Dimensions shown in mm are not binding and may be changed without notice.