

Part number
JCNLZ 06 PO



Complete connector, JNZ series, composed of 2 screw terminal connection inserts with 6 poles + PE, and surface mounting housing with 1 lever and hood with side cable entry

Product description		Material properties	
Product type	Complete connector	Colour	RAL 7040 grey
Series	JNZ		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Connection type	Screw terminal connection	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Size	Size 44.27	China RoHs - EFUP	50
N. of poles	6 poles + \perp	REACH SVHC substances	Yes
Cable entry	Pg16 x 2		Lead
Specification	Surface mounting housing with 1 lever and hood with side cable entry	SCIP number	A54fce24-f9c5-479f-a7e4-adb75fec7abe
Technical data		General ordering information	
Current	16 A	EAN13 code	8015747164498
Voltage	500 V	Packaging Information	
Rated impulse withstand voltage	6 kV	Packaging length	325,00 mm
Pollution degree	3	Packaging height	280,00 mm
Wire cross-section	0,50 mm ² - 4,00 mm ²	Packaging width	315,00 mm
AWG size	20 - 12	Packaging weight	8,20 kg
Contact type	Turned tin plated	Packaging volume	28,67 dm ³
IP degree of protection	IP66	Packaging description	Carton box
Further technical details		Packaging quantity	20 Pcs
Characteristics according to EN 61984	16 A 500 V 6 kV 3	Packaging EAN code	8015747165716
Mating cycles	≥ 200	Sub-packaging weight	0,41 kg
Insulation resistance	≥ 10 GΩ	Sub-packaging description	Plastic bag
Contact resistance	≤ 1 mΩ	Sub-packaging quantity	1 Pcs
Weight	407,00 g	Sub-packaging EAN barcode	8015747223942
Operating temperature range (min, max)	-40 °C ... +125 °C		
Conductors stripping length	7 mm		

Part number

JCNLZ 06 PO



Notes

Dimensions shown in mm are not binding and may be changed without notice.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.
