


Part number

KI 1675 IB6



Interlocked switched socket-outlet, IB6 series,
3 poles + PE, 7 h (black), 16 A, 480 ÷ 500 V,
sectionable fuse carrier 10 x 38 mm

Product description

Product type	Interlocked switched socket-outlet
Series	KI...IB6
N. of poles	3 poles + 
Clock position	7
Cable entry	M25
Specification	Sectionable fuse carrier 10 x 38 mm

Technical data

Current	16 A
Voltage	480 ÷ 500 V
IP degree of protection	IP66

Further technical details

Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7035 grey, RAL 9005 black
---------------	-------------------------------

Approvals / Standards

Reference standard	EN 60309-1, -2 e -4
---------------------------	---------------------

General ordering information

EAN13 code	8015747199452
-------------------	---------------

Part number

KI 1675 IB6



Notes

Dimensions shown in mm are not binding and may be changed without notice.

-
- Compliant with EN 60309-1, 2 e 4
 - Enclosures and inserts in insulating self-extinguishing thermoplastic material, RAL 7035 grey
 - 16A and 32A types with spring lid
 - Factory installed internal wiring
 - Cable entry with threaded metric opening
 - "ZF" series switch, with 32A rating
 - Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
 - Lockable switch
 - Compartment with sectionable fuse carrier (fuses not supplied) 10 x 38 mm (16A and 32A versions) or 22 x 58 mm (63A version) and clear inspection panel openable: only when the switch is off.
-