


Part number

# KI 3244 RI5



Interlocked switched socket-outlet, KI series, 3 poles + PE, 4 h (yellow), 32 A, 100 ÷ 130 V, with compartment for modular units, 7 DIN-rail modules EN 60715

Product description	
<b>Product type</b>	Interlocked switched socket-outlet
<b>Series</b>	KI..RI5
<b>N. of poles</b>	3 poles + 
<b>Clock position</b>	4
<b>Size</b>	143x343 fixing plates FC xx53 TB
<b>Cable entry</b>	Pg29
<b>Specification</b>	With compartment for modular units, 7 DIN-rail modules EN 60715

Technical data	
<b>Current</b>	32 A
<b>Voltage</b>	100 ÷ 130 V
<b>IP degree of protection</b>	IP55

Further technical details	
<b>Weight</b>	1.800,00 g
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C
<b>IK rating (impact degree of protection)</b>	IK10

Material properties	
<b>Colour</b>	RAL 7035 grey, RAL 1021 yellow
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	F6799547-ab84-42f2-938f-233ba663766d

Approvals / Standards	
<b>Reference standard</b>	EN 60309-1, -2 e -4

General ordering information	
<b>EAN13 code</b>	8015747049108

Packaging Information	
<b>Packaging length</b>	400,00 mm
<b>Packaging height</b>	165,00 mm
<b>Packaging width</b>	170,00 mm
<b>Packaging weight</b>	1,80 kg
<b>Packaging volume</b>	11,22 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	1 Pcs
<b>Packaging EAN code</b>	8015747049115

Part number

# KI 3244 RI5



## Catalogue drawings



## Notes

Dimensions shown in mm are not binding and may be changed without notice.

---