


Part number

# KI 3245 IB6



Interlocked switched socket-outlet, IB6 series,  
3 poles + N + PE, 4 h (yellow), 32 A, 100 ÷  
130 V, sectionable fuse carrier 10 x 38 mm

#### Product description

<b>Product type</b>	Interlocked switched socket-outlet
<b>Series</b>	KI...IB6
<b>N. of poles</b>	3 poles + N + 
<b>Clock position</b>	4
<b>Size</b>	114x228 fixing plates FC xx41 TB
<b>Cable entry</b>	M25
<b>Specification</b>	Sectionable fuse carrier 10 x 38 mm

#### Technical data

<b>Current</b>	32 A
<b>Voltage</b>	100 ÷ 130 V
<b>IP degree of protection</b>	IP66

#### Further technical details

<b>Operating temperature range (min, max)</b>	-25°C ... +40°C
<b>IK rating (impact degree of protection)</b>	IK10

#### Material properties

<b>Colour</b>	RAL 7035 grey, RAL 1021 yellow
---------------	--------------------------------

#### Approvals / Standards

<b>Reference standard</b>	EN 60309-1, -2 e -4
---------------------------	---------------------

#### General ordering information

<b>EAN13 code</b>	8015747199582
-------------------	---------------

Part number

# KI 3245 IB6



---

## Notes

Dimensions shown in mm are not binding and may be changed without notice.

- 
- Compliant with EN 60309-1, 2 e 4
  - Enclosures and inserts in insulating self-extinguishing thermoplastic material, RAL 7035 grey
  - 16A and 32A types with spring lid
  - Factory installed internal wiring
  - Cable entry with threaded metric opening
  - "ZF" series switch, with 32A rating
  - Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
  - Lockable switch
  - Compartment with sectionable fuse carrier (fuses not supplied) 10 x 38 mm (16A and 32A versions) or 22 x 58 mm (63A version) and clear inspection panel openable: only when the switch is off.
-