


Part number

KI 3275 IB6



Interlocked switched socket-outlet, IB6 series, 3 poles + N + PE, 7 h (black), 32 A, 200/346 ÷ 240/415 V, sectionable fuse carrier 10 x 38 mm

Product description

Product type	Interlocked switched socket-outlet
Series	KI...IB6
N. of poles	3 poles + N + 
Clock position	7
Cable entry	M25
Specification	Sectionable fuse carrier 10 x 38 mm

Technical data

Current	32 A
Voltage	480 ÷ 500 V
IP degree of protection	IP66

Further technical details

Weight	1.000,00 g
Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7035 grey, RAL 9001 black
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead

General ordering information

EAN13 code	8015747233743
-------------------	---------------

Packaging Information

Packaging length	560,00 mm
Packaging height	330,00 mm
Packaging width	270,00 mm
Packaging weight	10,00 kg
Packaging volume	49,90 dm ³
Packaging description	Carton box
Packaging quantity	8 Pcs
Packaging EAN code	8015747233750
Sub-packaging length	270,00 mm
Sub-packaging height	125,00 mm
Sub-packaging width	120,00 mm
Sub-packaging weight	1,25 kg
Sub-packaging volume	4,05 dm ³
Sub-packaging description	Carton box
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747233767

Part number

KI 3275 IB6



Notes

Dimensions shown in mm are not binding and may be changed without notice.

-
- Compliant with EN 60309-1, 2 e 4
 - Enclosures and inserts in insulating self-extinguishing thermoplastic material, RAL 7035 grey
 - 16A and 32A types with spring lid
 - Factory installed internal wiring
 - Cable entry with threaded metric opening
 - "ZF" series switch, with 32A rating
 - Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
 - Lockable switch
 - Compartment with sectionable fuse carrier (fuses not supplied) 10 x 38 mm (16A and 32A versions) or 22 x 58 mm (63A version) and clear inspection panel openable: only when the switch is off.
-