

Part number

MFVN 06 LG25



Hood, LS-TYPE series, with 1 lever, M25 top cable entry without adapter, size "44.27", high construction

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 1 lever
Size	Size 44.27
Cable entry	Top cable entry M25
Specification	High construction

Technical data

IP degree of protection	IP65
Further technical details	
Weight	170,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747187398
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information


Sub-packaging weight	0,85 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747188180

Part number

MFVN 06 LG25



Catalogue drawings



Catalogue drawings

CH..N - MF..N enclosures size "44.27" LS-TYPE version

<p>inserts: page</p> <p>CDD 24 poles + @ 59 *</p> <p>CQE 10 poles + @ 80 *</p> <p>CSH 6 poles + @ 88 *</p> <p>CCE 6 poles + @ 94 *</p> <p>CNE, CSE, JONE, JCSE 6 poles + @ 95 and 103 *</p> <p>CSS 6 poles + @ 118 *</p> <p>MIXO 2 modules 160+195 *</p> <p>insert centre distance: 44 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p>hoods with 2 pegs</p>	<p>covers</p>
description	part no. entry	part no.
with lever and gasket, top entry with lever and gasket, top entry, high construction	MHVN 06 LG25 25 MFVN 06 LG25 25	
covers with pegs covers with lever		CHCN 06 L CHCN 06 LG
	<p>dimensions in mm</p> <p>MHVN 06 LG25</p> <p>MFVN 06 LG25</p>	<p>dimensions in mm</p> <p>CHCN 06 L</p> <p>CHCN 06 LG</p>
<p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>		

dimensions shown are not binding and may be changed without notice

Notes

Dimensions shown in mm are not binding and may be changed without notice.