

Part number

MHON 06 L25



Hood, LS-TYPE series, with 2 pegs, M25 side cable entry, size "44.27"

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 2 pegs
Size	Size 44.27
Cable entry	Side cable entry M25

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	95,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747194181
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information

Sub-packaging weight	0,48 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747194198

Part number MHON 06 L25



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "44.27" **LS-TYPE version**

inserts:	page	housings with single lever	hoods with 2 pegs
CDD	24 poles + ⊕ 59 *		
CQE	10 poles + ⊕ 80 *		
CSH	6 poles + ⊕ 88 *		
CCE	6 poles + ⊕ 94 *		
CNE, CSE, JONE, JOSE	6 poles + ⊕ 95 and 103 *		
CSS	6 poles + ⊕ 118 *		
CTE, CTSE **)	6 poles + ⊕ 126 *		
MIXO	2 modules 160+195 *		

insert centre distance: 44 x 27 mm
* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with lever	CHIN 06 L	M		
surface mounting housing, high construction, with lever	MAPN 06 L32	32		
with pegs, side entry			MHON 06 L25	25
with pegs, side entry, high construction			MFON 06 L25	25
with pegs, top entry			MHVN 06 L25	25
with pegs, top entry, high construction			MFVN 06 L25	25

**) only in the CHIN 06 L enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

IP65

dimensions shown are not binding and may be changed without notice

4

Notes

Dimensions shown in mm are not binding and may be changed without notice.