

Part number

# MHVN 06 LG25



Hood, LS-TYPE series, with 1 lever, M25 top cable entry, size "44.27"


Product description		Material properties	
<b>Product type</b>	Hood	<b>Other materials</b>	Lever: Polyamide (PA) Gasket: NBR
<b>Series</b>	LS-TYPE	<b>Colour</b>	RAL 9005 black
<b>Closing type</b>	With 1 lever	<b>RoHs conformity</b>	Compliant
<b>Size</b>	Size 44.27	<b>China RoHs - EFUP</b>	E
<b>Cable entry</b>	Top cable entry M25	<b>REACH SVHC substances</b>	No
Technical data		Approvals / Standards	
<b>IP degree of protection</b>	IP65	<b>Certifications</b>	DNV, BV
Further technical details		<b>UL</b>	ECBT2
<b>Weight</b>	124,00 g	<b>cUL</b>	ECBT8
<b>Operating temperature range (min, max)</b>	-40°C...+125°C	General ordering information	
		<b>EAN13 code</b>	8015747194341
		<b>eCl@ss 8.1</b>	27440202
		<b>ETIM 7.0</b>	EC000437
		Packaging Information	
		<b>Sub-packaging weight</b>	0,62 kg
		<b>Sub-packaging description</b>	Plastic packaging
		<b>Sub-packaging quantity</b>	5 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747194358

Part number

# MHVN 06 LG25



Catalogue drawings



Catalogue drawings

CH..N - MF..N enclosures		size "44.27"	LS-TYPE version																					
<p>inserts:</p> <table border="0"> <tr> <td>CDD</td> <td>24 poles + @</td> <td>59 *</td> </tr> <tr> <td>CQE</td> <td>10 poles + @</td> <td>80 *</td> </tr> <tr> <td>CSH</td> <td>6 poles + @</td> <td>88 *</td> </tr> <tr> <td>CCE</td> <td>6 poles + @</td> <td>94 *</td> </tr> <tr> <td>CNE, CSE, JONE, JCSE</td> <td>6 poles + @ 95 and 103</td> <td>118 *</td> </tr> <tr> <td>CSS</td> <td>6 poles + @</td> <td>118 *</td> </tr> <tr> <td>MIXO</td> <td>2 modules</td> <td>160+195 *</td> </tr> </table> <p>insert centre distance: 44 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	CDD	24 poles + @	59 *	CQE	10 poles + @	80 *	CSH	6 poles + @	88 *	CCE	6 poles + @	94 *	CNE, CSE, JONE, JCSE	6 poles + @ 95 and 103	118 *	CSS	6 poles + @	118 *	MIXO	2 modules	160+195 *	<p>hoods with 2 pegs</p>	<p>covers</p>	
CDD	24 poles + @	59 *																						
CQE	10 poles + @	80 *																						
CSH	6 poles + @	88 *																						
CCE	6 poles + @	94 *																						
CNE, CSE, JONE, JCSE	6 poles + @ 95 and 103	118 *																						
CSS	6 poles + @	118 *																						
MIXO	2 modules	160+195 *																						
<p>description</p> <p>with lever and gasket, top entry with lever and gasket, top entry, high construction</p>	<p>part no.</p> <p>MHVN 06 LG25 25 MFVN 06 LG25 25</p>	<p>entry</p> <p>M</p>	<p>part no.</p> <p>CHCN 06 L CHCN 06 LG</p>																					
<p>covers with pegs covers with lever</p>	<p>dimensions in mm</p> <p>MHVN 06 LG25</p> <p>MFVN 06 LG25</p>	<p>dimensions in mm</p> <p>CHCN 06 L</p> <p>CHCN 06 LG</p>																						
<p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>																								
<p>dimensions shown are not binding and may be changed without notice</p>																								

## Notes

Dimensions shown in mm are not binding and may be changed without notice.