


Part number

# PE 16114 SV



Mobile plug, PLUSO series, 3 poles + PE, 11 h (red), 16 A, 440 ÷ 460 V, straight

Product description		Material properties	
<b>Product type</b>	Plug Mobile	<b>Colour</b>	RAL 7035 grey, RAL 3000 red
<b>Series</b>	PE...SV, PLUSO	<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>Connection type</b>	Screw terminal connection	<b>China RoHs - EFUP</b>	50
<b>N. of poles</b>	3 poles + 	<b>REACH SVHC substances</b>	Yes Lead
<b>Clock position</b>	11	<b>SCIP number</b>	Ca7de37f-add8-4b77-9861-279c94903ade
<b>Specification</b>	Straight	Approvals / Standards	
Technical data		<b>Reference standard</b>	EN 60309-1 and -2
<b>Current</b>	16 A	General ordering information	
<b>Voltage</b>	440 ÷ 460 V	<b>EAN13 code</b>	8015747062893
<b>IP degree of protection</b>	IP44	Packaging Information	
Further technical details		<b>Packaging length</b>	208,00 mm
<b>Weight</b>	126,00 g	<b>Packaging height</b>	140,00 mm
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Packaging width</b>	290,00 mm
		<b>Packaging weight</b>	1,47 kg
		<b>Packaging volume</b>	8,44 dm <sup>3</sup>
		<b>Packaging description</b>	Carton box
		<b>Packaging quantity</b>	10 Pcs
		<b>Packaging EAN code</b>	8015747234405


Part number

# PE 16114 SV



Catalogue drawings

(16 / 32A) PE ... SV



PE ... SV	A	B	Ø min	Ø max	
<b>16A</b> 2P+⊕	143,5	59	7	17	
	3P+⊕	148,5	66	7	17
	3P+N+⊕	167,5	75	9	22
<b>32A</b> 2P+⊕	187	80	9	22	
	3P+⊕	187	80	9	22
	3P+N+⊕	192,5	87	9	22

## Notes

Dimensions shown in mm are not binding and may be changed without notice.