


Part number

PE 1654 SV



Mobile plug, PLUSO series, 3 poles + PE, 5 h (black), 16 A, 600 ÷ 690 V, straight

Product description		Material properties	
Product type	Plug Mobile	Colour	RAL 7035 grey, RAL 9005 black
Series	PE...SV, PLUSO	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Connection type	Screw terminal connection	China RoHs - EFUP	50
N. of poles	3 poles + 	REACH SVHC substances	Yes Lead
Clock position	5	SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade
Specification	Straight	Approvals / Standards	
Technical data		Reference standard	EN 60309-1 and -2
Current	16 A	General ordering information	
Voltage	600 ÷ 690 V	EAN13 code	8015747064309
IP degree of protection	IP44	Packaging Information	
Further technical details		Packaging length	208,00 mm
Weight	121,00 g	Packaging height	140,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Packaging width	290,00 mm
		Sub-packaging weight	1,21 kg
		Sub-packaging description	Carton box
		Sub-packaging quantity	10 Pcs
		Sub-packaging EAN barcode	8015747064316


Part number

PE 1654 SV



Catalogue drawings

(16 / 32A) PE ... SV



PE ... SV	A	B	Ø min	Ø max	
16A 2P+⊕	143,5	59	7	17	
	3P+⊕	148,5	66	7	17
	3P+N+⊕	167,5	75	9	22
32A 2P+⊕	187	80	9	22	
	3P+⊕	187	80	9	22
	3P+N+⊕	192,5	87	9	22

Notes

Dimensions shown in mm are not binding and may be changed without notice.