


Part number

PE 3244 PV



Mobile socket outlet, PLUSO series, 3 poles + PE, 4 h (yellow), 32 A, 100 ÷ 130 V

Product description

Product type	Socket Mobile
Series	PE...PV, PLUSO
N. of poles	3 poles + 
Clock position	4

Technical data

Current	32 A
Voltage	100 ÷ 130 V
IP degree of protection	IP44

Further technical details

Weight	236,00 g
Operating temperature range (min, max)	-25°C ... +40°C

Material properties

Colour	RAL 7035 grey, RAL 1021 yellow
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade

Approvals / Standards

Reference standard	EN 60309-1 and -2
---------------------------	-------------------

General ordering information

EAN13 code	8015747066860
-------------------	---------------

Packaging Information

Packaging length	330,00 mm
Packaging height	175,00 mm
Packaging width	295,00 mm
Packaging weight	2,74 kg
Packaging volume	17,04 dm ³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747066877


Part number

PE 3244 PV



Catalogue drawings

(16 / 32A) PE ... PV



PE...PV	A	B	Ø min	Ø max	
16A 2P+⊕	157,5	68	7	17	
	3P+⊕	164,5	76	7	17
	3P+N+⊕	183,5	83	9	22
32A 2P+⊕	200,5	87	9	22	
	3P+⊕	200,5	87	9	22
	3P+N+⊕	200,5	91	9	22

Notes

Dimensions shown in mm are not binding and may be changed without notice.