

Part number

PE 3293 PV



Mobile socket outlet, PLUSO series, 2 poles + PE, 9 h (red), 32 A, 380 ÷ 415 V

Product description		Material properties	
Product type	Socket Mobile	Colour	RAL 7035 grey, RAL 3000 red
Series	PE...PV, PLUSO	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	2 poles + 	China RoHs - EFUP	50
Clock position	9	REACH SVHC substances	Yes Lead
Technical data		SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade
Current	32 A	Approvals / Standards	
Voltage	380 ÷ 415 V	Reference standard	EN 60309-1 and -2
IP degree of protection	IP44	General ordering information	
Further technical details		EAN13 code	8015747067980
Weight	217,00 g	Packaging Information	
Operating temperature range (min, max)	-25°C ... +40°C	Packaging length	285,00 mm
		Packaging height	170,00 mm
		Packaging width	190,00 mm
		Packaging weight	2,49 kg
		Packaging volume	9,21 dm ³
		Packaging description	Carton box
		Packaging quantity	10 Pcs
		Packaging EAN code	8015747067997


Part number

PE 3293 PV



Catalogue drawings

(16 / 32A) PE ... PV



PE...PV		A	B	Ø min	Ø max
16A	2P+⊕	157,5	68	7	17
	3P+⊕	164,5	76	7	17
	3P+N+⊕	183,5	83	9	22
32A	2P+⊕	200,5	87	9	22
	3P+⊕	200,5	87	9	22
	3P+N+⊕	200,5	91	9	22

Notes

Dimensions shown in mm are not binding and may be changed without notice.