

Part number

PEW 1634 SV



Mobile plug, PLUSO series, 3 poles + PE, 3 h (red), 16 A, 380 ÷ 380 V, straight

Product description		Material properties	
Product type	Plug Mobile	Colour	RAL 7035 grey, RAL 3000 red
Series	PEW...SV, PLUSO	Approvals / Standards	
N. of poles	3 poles + 	Reference standard	EN 60309-1 and -2
Clock position	3	General ordering information	
Specification	Straight	EAN13 code	8015747157049
Technical data		Packaging Information	
Current	16 A	Packaging length	208,00 mm
Voltage	380V (50Hz.) 440V (60Hz.)	Packaging height	140,00 mm
IP degree of protection	IP67	Packaging width	290,00 mm
Further technical details		Packaging volume	8,44 dm ³
Weight	1,00 g	Packaging description	Carton box
Operating temperature range (min, max)	-25°C ... +40°C	Packaging quantity	10 Pcs
		Packaging EAN code	8015747303446


Part number

PEW 1634 SV



Catalogue drawings

(16 / 32A) PEW ... SV



PEW ... SV		A	B	Pg Ø
16A	2P+⊕	137	70	16
	3P+⊕	142	78	16
	3P+N+⊕	150	86	21
32A	2P+⊕	170	92	21
	3P+⊕	170	92	21
	3P+N+⊕	175	99,5	21

Notes

Dimensions shown in mm are not binding and may be changed without notice.

32A only version PHW...SV)

- Compliant with EN 60309-1 and -2
- Enclosure, insert and locking ring in insulating, thermoplastic, self-extinguishing material
- PE...SV types 16A and 32A (IP44), entry with cable gland colour coded according to the operating voltage, RAL 7035 grey enclosure
- PEW...SV types 16A and 32A (IP66/IP67), entry with cable gland colour coded according to the operating voltage, RAL 7035 grey enclosure, locking ring with gasket colour coded according to operating voltage
- PEW...SV types 63A and 125A (IP67), entry with cable gland, RAL 7035 grey enclosure, locking ring with gasket colour coded according to operating voltage
- PEW...SV types 63A and 125A (IP67), cable anchoring collar incorporated in the insert
- SIP version with phase inverter (3P+N+E, h6), 16A and 32A
- Terminals with retained screws
- 63A, 125A: with pilot contact
- Nickel-plated contacts standard on 63A and 125A (on 16A and