Part number PEW 1635 PI





Flush-mounting socket outlet, PLUSO series, 3 poles + N + PE, 3 h (red), 16 A, 380 V, inclined

Product description		Material properties					
Product type	Socket	Colour	RAL 7035 grey, RAL 3000 red				
	Flush-mounting	Approvals / Standards					
Series	PEWPI, PLUSO	Reference standard	EN 60309-1 and -2				
N. of poles	3 poles + N + 🖶	General ordering inform	General ordering information				
Clock position	3	EAN13 code	8015747157056				
Specification	Inclined						
Technical data							
Current	16 A						
Voltage	220/380V (50Hz) 250/440V (60Hz)						
IP degree of protection	IP67						
Further technical details							

Operating temperature range (min, max)


-25°C ... +40°C





Catalogue drawings

(16 / 32A) PEW ... PI



PEW	PI	Α	В	С	D	Е	F	G	н	I	Х	Y
16A	2P+⊕	65	82	83	48	35	70	50	29	58	52	60
	3P+⊕	65	82	87	48	37	78	58	30	65	52	60
	3P+N+⊕	90	100	102	50	38	86	66	35	75	77	85
32A	2P+⊕	90	100	116	50	50	92	68	37	78	77	85
	3P+⊕	90	100	116	50	50	92	68	37	78	77	85
	3P+N+⊕	90	100	118	50	50	100	73	42.5	86	77	85

Notes

Dimensions shown in mm are not binding and may be changed without notice.

- Compliant with EN 60309-1 and -2

- Enclosure, insert and spring lid in insulating, thermoplastic, selfextinguishing material

- RAL 7035 grey enclosure, spring lid colour coded according to the operating voltage

- Flange with anti-ageing gasket
- PE...PI types (IP44), spring lid
- PEW...PI types (IP67), spring lid with locking ring and gasket
- Terminals with retained screws
- 63A, 125A: with pilot contact

- Nickel-plated contacts, available on request for 16A and 32A (standard on 63A and 125A). For the code of products with nickelplated contacts (socket holes, plug pins), add "N" to the pre-code of the corresponding standard product code; for example: PE becomes PEN and PEW becomes PEWN.

- IP44 and IP67 degrees of protection (EN 60529)